TOILETS

Wall Hung Toilet Pan - Access Compliant

Model: SPPL.TP.WH.4.D

- SPPL = Stoddart Plumbing Product
- TΡ = Toilet Pan WH.4 = Wall Hung Type 4
- = Disabled Access D
- eg.: for specification and ordering quote
- Code: SPPL.TP.WH.4.D

Features and Benefits:

- Hydraulically formed seat with smooth radius to inner and outer edges for safety and comfort.
- Seat area is sloped to drain into the bowl for improved hygiene
- Heavy duty (500kg) load carrying capacity (depending on wall structure)
- Concealed plumbing and fixing points for security and vandal resistance Engineered flushing rim prevents hiding of contraband while allowing free flow of flush water
- Powder coated to colour of choice optional
- Optional 316 grade stainless steel suitable for highly corrosive and coastal environments
- These toilets can be flushed with either a flush valve or in-wall cistern (ordered separately)
- Access compliant when mounted at correct height



Toilet bowl and Trap – 304 stainless steel. Seat, Body and shroud – 2mm 304 stainless

WELS approved 4.5L full flush/3L half flush.

Flushing device must be able to deliver 1.4 litres per second to the toilet pan (as per

Inlet Key-Seal supplied for 40mm flush pipe.


The unit is designed to be fixed to the rear wall with 4×016 stainless steel bolts.


P trap standard, with rubber coupling included

steel no.4 satin finish

to suit 100mm PVC.

AS1172).







5mm S/S Rear Fixing Plate

Plan View

Rear View





End View

Front View

()

FD.CI.IW.MDF

FD.CI.IW.PRF



Sold Separately

Flushing Device Options:

FD.CI.IW.EFV

Toilet Seat Options:



CMPL.1005

FD.CI.IW.PRF.CB

CMPL.0814

CMPL.0915











Specifications:

Water Connection:

Waste Connection:

Unit Fixing:

Construction:

Flushing:

Due to continuous product research and development, the information contained herein is subject to change without notice. Revision: A3 - 16/06/23

www.stoddart.com.au www.stoddart.co.nz

