

AXR.UCGN.3G

Refrigerated Undercounter 3 Glass Doors - 1/1GN

Product Information:

- Monoblock refrigeration system, for improved performance and ease of servicing
- Adjustable digital temperature controller (0°C 6°C)
- Unique fan forced ducted cooling for uniformed performance throughout the entire refrigerator
- · Protective coating on refrigeration coil to help prevent corrosion
- Environmentally friendly R290 Hydrocarbon refrigerant
- · Efficient LED lighting for increased product visibility
- Stainless Steel worktop as standard, 840mm finish height. (Optional 900mm working height model available)
- 1/1GN shelf configuration with adjustable runners (2 shelves per door)
- 60mm CFC free polyurethane insulation
- Efficient and hygienic cleaning made easy with an innovative internal design
- High quality components including highly efficient compressors and EC fans
- Double glazed heated glass door for exceptional display and minimal condensation. Self-closing, lockable doors
- · Removable filter for easy cleaning
- Equipped standard with lockable castors designed for heavy-duty use
- 2 and 4 door models also available, with glass or solid doors

Designed and Engineered in Australia to meet Australian Standards 24 Months on-site parts and labour warranty

Optional Accessories:

• 1/1GN shelf with runners (AXR.UCGN.SHELFKIT)

Specifications

 Model
 AXR.UCGN.3G

 W x D x H (mm)
 1795 x 700 x 840

Weight 133kg

Packed Dimensions (mm) $1825 \times 730 \times 880$

Packed Weight157kgNet Capacity276 Litres

 Operation
 0°C - 6°C

 Refrigerant
 R290

 Climate Class
 4M1

Energy Consumption 4.24kWh/24hr

Max Ambient 38°C

Total Connected Load 0.41kW


Electrical Connection 230VAC / 50Hz / (10A plug & lead)


Due to continuous product research and development, the information contained herein is subject to change without notice.

Revision: C - 19/09/2023 - 01

www.stoddart.com.au www.stoddart.co.nz







FRONT VIEW

