





- Unit designed to be installed into a new or existing bench top cut-out.
 Complete with, A-Frame 304 stainless steel gantry. (Gantry welded to bench top)
- Wet or dry operation (temperature varies greatly when run dry, should not be left unattended for long periods of time)
- Temperature regulation via digital control, designed to hold product between 65°C - 90°C.
- · Independent controlls for baine marie, hot cupboard and gantry
- · A-frame gantry fitted with Quartz IR heat lamps
- Air insulated, double skinned tank for energy efficient heating
- Gantry constructed from 304 grade stainless steel with a No.4 finish and 6mm toughened glass end
- Manual fill and manual empty, valve operated waste
- 1/1 GN sized well, fits pans up to 150mm deep (sold separately).
 Supplied with pan dividers
- · 12-month parts and labour warranty



Specifications:

 Model
 CH.BM.D.GA.8

 W x D x H (mm)
 2837 x 647 x 760

 Cutout Dimensions (mm)
 2815 x 625

Total Connected Load 7.8kW

Electrical Connection 3Ø+N+E 400VAC / 50Hz

(Onsite connection)

Water Connection G 1/2" BSP
Waste Connection 11/4" BSP

Optional Extras:

Radius Well

Add **R** to code after the **D** CH.BM.D**R**.GA.8

Front Glass CA.GAF.8
Sliding Doors CA.GAD.8
Sneeze Guards CA.GAS.8

Note: Optional extras must be selected at time of order

Accessories:

Large Pan Dividers CA.PXL

(To suit large GN pans)

Cross Pan Dividers CA.PXS

(To suit smaller GN pans)

Legend:

- A Electrical Connection
- **B** Water Connection
- C Waste Connection











