

Bain Marie - Drop-In CH.BM.D.5



- This unit is designed to be installed into a cut-out in a new or existing bench top
- Wet or dry operation (temperature varies greatly when run dry, should not be left unattended for long periods of time)
- Temperature regulation via digital control, designed to hold product between 65°C - 90°C.
- Air insulated, double skinned tank for energy efficient heating
- Robust 304 grade stainless steel construction
- Manual fill and manual empty, valve operated waste
- 1/1 GN sized well, fits pans up to 150mm deep (sold separately). Supplied with pan dividers
- 12-month parts and labour warranty



Specifications:

CH BM D 5 1817 x 647 x 284 WxDxH(mm) 1795 x 625 **Cutout Dimensions (mm)**

Total Connected Load 375kW

1Ø+N+E 240VAC / 50Hz **Electrical Connection**

(Onsite connection)

Water Connection G 1/2" BSP 11/4" BSP **Waste Connection**

Optional Extras:

Radius Well

Add **R** to code after the **D** CH.BM.DR.5 Note: Radius Well must be nominated at time of order

Accessories:

Large Pan Dividers CA.PXL (To suit large GN pans)

Cross Pan Dividers CA.PXS (To suit smaller GN pans)

Legend:

Electrical Connection

Water Connection

Waste Connection











