

Product Information:

- High performance XL hood-type dishwasher
- **E-Management:** intuitive and advanced electronic interface
- **PRS System:** break tank, 316 atmospheric boiler, rinse booster pump
- **HD System:** for maximum uninterrupted performance
- Increased capacity with 600x500mm baskets (500x500mm compatible)
- XL Filters robust and additional upper tank scrap filters in stainless steel
- Larger HP vertical self-draining wash pump
- Larger HI FLOW stainless steel wash and rinse arms
- Larger elements in wash tank and boiler
- Four wash cycles 90/120/180 seconds, and 9 minute deep clean
- Green standby function that reduces energy consumption when idle
- Low water consumption of 2.5 litres per cycle, minimising water, energy and detergent use
- Pressed wash tank with rounded corners, for increased hygiene
- Manual lift with fully enclosed rear, 3 spring support
- Automatic drain pump with self-cleaning function
- Built in thermostop, ensures correct rinse temperatures
- Built in detergent and rinse-aid injection
- **18-months parts and labour warranty**



Included Accessories:

- 1 x glass rack 500x600mm
- 2 x plate rack 500x600mm
- 2 x cutlery basket
- 1 x water inlet hose (length 1.5m)
- 1 x drain hose (length 2m)
- Fitted with 150mm adjustable legs

Optional Accessories:

- Twin hood system
- Remote interface
- Inlet and outlet benches
- Additional baskets

Specifications:

Model	AH60.42EPRS
W x D x H (mm)	657 x 793 x 2016
Note:	Dimensions do not include handle. Hood open
Weight	141kg
Packed Dimensions (mm)	770 x 930 x 1720
Packed Weight	160kg

Total Connected Load	14.8kW
- Convertible to:	10.3kW (low power option)

Note: Unit can be converted to low power option on site by a qualified electrician. This may affect the output of the unit.

Electrical Connection	3Ø+N+E 415VAC / 50Hz (Lead fitted, onsite connection)
------------------------------	----------------------------------------------------------

Water Quantity Per Cycle	2.5 Litres
Water Connection	1.5m Hose / 3/4" BSP
Water Inlet Pressure	100 - 500KPA
Tempered water supply	10°C - 60°C
Waste Connection	2m Hose / ø20.5mm

Legend:

- A Electrical Connection
- B Water Connection
- C Drain Connection
- D Detergent Connection
- E Rinse-Aid Connection

