airex∋

AXF.UCGN.2

Freezer Undercounter 2 Door - 1/1GN

Product Information:

- Monoblock refrigeration system, for improved performance and ease of servicing
- Adjustable digital temperature controller (^{-16°} ^{-20°}C)
- Unique fan forced ducted cooling for uniformed performance throughout the entire freezer
- Protective coating on refrigeration coil to help prevent corrosion
- Environmentally friendly R290 Hydrocarbon refrigerant
- Efficient LED lighting for increased product visibility
- Stainless Steel worktop as standard, 840mm finish height. (Optional 900mm working height model available)
- 1/IGN shelf configuration with adjustable runners (2 shelves per door)
- 60mm CFC free polyurethane insulation
- Efficient and hygienic cleaning made easy with an innovative internal design
- High quality components including highly efficient compressors
 and EC fans
- Self-closing, lockable doors
- Removable filter for easy cleaning
- Equipped standard with lockable castors designed for heavy-duty use
- 3 door model also available, with glass or solid doors

Designed and Engineered in Australia to meet Australian Standards 24 Months on-site parts and labour warranty

Optional Accessories:


• 1/1GN shelf with runners (AXR.UCGN.SHELFKIT)


Specifications

Model	AXF.UCGN.2
W x D x H (mm)	1360 x 700 x 840
Weight	107kg
Packed Dimensions (mm)	1390 x 730 x 880
Packed Weight	126kg
Net Capacity	184 Litres
Operation	-16°C20°C
Refrigerant	R290
Climate Class	4L1
Energy Consumption	7.2kWh/24hr
Max Ambient	38°C
Total Connected Load	0.64kW
Electrical Connection	230VAC / 50Hz / (10A plug & lead)

Due to continuous product research and development, the information contained herein is subject to change without notice. Revision: C - 28/02/2024 - 01

www.stoddart.com.au www.stoddart.co.nz





FRONT VIEW

-



