DRINKING FOUNTAINS

Metro Dual - Chilled Wall Mounted

Model: SPPL.DF.MD.WM.HC

SPPL = Stoddart Plumbing Product
DF = Drinking Fountain

DF = Drinking Fountain
MD = Metro Dual
WM = Wall Mounted
HC = Hinged & Chilled

eg.: for specification and ordering quote

Code: SPPL.DF.MD.WM.HC



Specifications:

Construction: 1.5mm 304 grade stainless steel construction,

no.4 satin finish. Unit is pre-plumbed with

button and bubbler

Water Connection: Single 15mm (1/2" BSP)
Waste Connection: 40mm waste connection

Unit Fixing: The unit is supplied with a stainless steel

hinged wall frame and mounting bracket. Access panels provide secured access to

plumbing under each fountain.

Disabled Access: The preferred fixing height for Disabled


Access is 850 - 890mm from the top of unit to finished floor level to allow clear leg space under the unit. This height is also suited for most adults, while 700mm provides access for


most children.

Model No.	L x D x H (mm)
SPPL.DF.MD.WM.HC	980 x 895 x 820


Features and Benefits:

- Ideal drinking fountain for schools, shopping malls, hospitals, airports and outdoor areas
- Easy-Push buttons & valves supply a regulated flow of fresh clean drinking water while reducing water waste
- Large rounded collection bowl prevents excess water on the ground
- Wall Mounted Drinking Fountain can be easily mounted to most wall surfaces at heights suitable to the application
- Wheelchair accessible as per the requirements advised in AS1428.2
- Configured with a vented wall panel for the chilled water unit as fitted
- All optional tapware are WELS and Watermark approved





Plan View



058

Front View

End View

Sold Separately

Tapware Options:




















039

