

4K HDMI POV CAMERA

**AIDA**  
IMAGING

# UHD-200

## Captures Superb Ultra-HD at 60 frames

Ahead of its time, the UHD-200 brings buttery smooth Ultra-HD video at 60 frames with no cost to affordability or performance. Never miss out on an unforgettable moment in live action sports and racing again!



**KEY FEATURES:**



**APPLICATIONS:**



LIVE PRODUCTION



WORSHIP



SPORTS



MEDICAL



THEATER

## MAIN FEATURES


- 4K 1/1.7 Progressive Scan CMOS sensor capable of 4K (4096 x 2160) captures sharp and vivid images even under very low light conditions.
- Power by a back-illuminated pixel technology.
- Advanced digital imaging processor provides vivid and detailed images by utilizing Dynamic Range, Auto White Balance, and Noise Reduction.
- Superb motion-compensated temporal noise reduction filter for motion video without blurring.
- OSD control breakout cable with two audio inputs and RS-485 for remote communication.
- Flawlessly relays multi-channel embedded audio via HDMI 2.0.
- Perfectly suited for broadcast, pro audio/video, and security.
- Versatile, compact, and rugged design.

## SPECIFICATIONS

<b>VIDEO</b>		<b>LENS</b>	
<b>Image Sensor</b>	1/1.7" inch Progressive CMOS	<b>Lens</b>	C/CS Mount (With 4K 3.6mm -11mm varifocal Lens)
<b>Sensor Size</b>	Diagonal 9.93mm (17:9)	<b>AUDIO INPUT</b>	
<b>Effective Pixels</b>	Horizontal: 4096, Vertical: 2160	<b>Input</b>	3.5mm TRS Stereo Mic-in & Line in over I/O Cable
<b>Pixel Size</b>	1.85 μm (H) x 1.85 μm (V)	<b>Sample Rate</b>	16/24/32 Bits
<b>Resolution</b>	4096 x 2160, 3840 x 2160, 1920 x 1080, 1280 x 720	<b>PHYSICAL</b>	
<b>Resolution Rate</b>	4K (4096 X 2160) 60/59.94/50/30/29.97/25/24 3840p 60/59.94/50/30/29.97/25/24p 1080p 60/59.94/50/30/29.97/25p/24p 1080i 60/59.94/50i 720 60/59.94/50p	<b>Camera Control</b>	RS-485, VISCA
<b>Output</b>	HDMI 2.0	<b>Operation Temp</b>	15°F - 120°F
<b>Color Space</b>	4:2:2 (YCbCr) 10bit	<b>Dimension</b>	51mm x 51mm x 102mm / 2.01" x 2.01" x 4.01"
<b>Min. Illumination</b>	0.2Lux (Day), 0.1Lux(Night) 0.005Lux(Slow Shutter ON)	<b>Weight</b>	384g / 0.84lbs
<b>White Balance</b>	Auto & Manual (9,000 K - 11,000K)	<b>Power</b>	12VDC (+9 - +15VDC)

*\*Specification are subject to change without notice.*

## PACKAGE CONTENTS



I/O Breakout Cable



DC 12v Power Supply & Sockets Adapter



3.6mm-11mm Varifocal Lens( Pre-Installed)



USB Cable



C-Mount Cap Adapter



Sensor Cap