

UHD6G-200

Comfortability with Conformability

The UHD6G-200 breathes life to any new, or existing SDI infrastructure with versatility, and uniqueness. With its rugged design, you may just forget it's even there in the studio



KEY FEATURES:









APPLICATIONS:











LIVE PRODUCTION WORSHIP RACING MEDICAL

FILM



MAIN FEATURES

- 4K UHD 1/2.5 Progressive Scan CMOS sensor captures sharp and vivid UHD video even under very low light conditions.
- Advanced digital imaging processor provides vivid and detailed images by utilizing Dynamic Range, Auto White Balance, and Noise Reduction.
- Superb motion-compensated temporal noise reduction filter for motion video without blurring.
- OSD control breakout cable with power input and RS-485 for remote communication.
- Flawlessly relays multi-channel embedded audio via SDI.
- Interchangeable lens design compatible with CS and C mount lenses.
- Perfectly suited for broadcast, pro audio/video, and security.
- Conforming with SMPTE 292M, 424M, and 2081-10.
- Versatile, compact, and rugged design.

SPECIFICATIONS

VIDEO

1/2.5" Progressive CMOS **Image Sensor Sensor Size** 8.365mm X 6.615mm (16:9) **Effective Pixels** Horizontal: 3840, Vertical: 2160 $1.62~\mu m$ (H) x $1.62~\mu m$ (V) **Pixel Size**

Resolution 3840 x 2160, 1920 x 1080, 1280 x 720

Resolution Rate 2160 30p/29.97p/25p/24p 1080 60p/59.94p/50p/30p/

> 29.97p/25p/24p 1080 60i/59.94i/50i

720 60p/59.94p/50p/30p/25p

Output HD/3G/6G-SDI (BNC) **Color Space** 4:2:2 (YCbCr) 10bit

FUNCTION

AWB / AE / AF White Balance

Exposure Full Auto, Bright, Shutter Priority,

Iris Priority, Manual

Other WDR, DIS (Digital Image Stabilization), 2D/3D

> Noise Reduction, Digital Slow Shutter, Black Level Compensation, Flicker Detection

LENS

C/CS Mount (Default UHD 3.2mm Lens) Lens

AUDIO

3.5mm TRS Stereo Audio via Camera Input Input

Sample Rate 16/24/32 Bits

PHYSICAL

Camera Control RS-486

OSD Button

Operation Temp 15°F - 120°F

Dimension 56m x 56mm x 71.90mm /

2.20" x 2.20" x 2.83"

Weight 170a / 0.37lbs

12VDC (+9 - +15VDC) Power

*Specification are subject to change without notice.

PACKAGE CONTENTS



I/O Breakout Cable




USB Cable



DC 12v Power Supply & Sockets Adapter



C-Mount Cap Adapter



3.2mm 12MP 4K Lens (Pre-installed)



Sensor Cap

At ADIA Imaging, innovation is key to crafting our tried and tested quality imaging solutions. We strive to raise the bar by engineering and manufacturing cutting edge cameras and converters.

From concept to reality, AIDA Imaging meticulously creates products that are applicable to various solutions, effective for the global user.