

## An Ultra-compact Document Solution with Wireless Connectivity

### High Productivity

- Reliable, flexible media handling supports cardstock, small media, and envelopes from the main tray or the multipurpose feeder
- Steel frame and lifetime imaging components mean long life and minimal maintenance

### Exceptional Ease of Use

- Two-line display lets you configure, interact with, and monitor vital system information
- SRDM (Sharp Remote Device Manager)\*<sup>1</sup> software allows centralised control of networked printers and MFDs
- Sharp's printer driver setup window features a user-friendly design
- Compact footprint\*<sup>2</sup> (368 x 363 mm)

### Secure Information Sharing

- Standard-equipped wireless connectivity enables easy access from mobile devices and flexible printer placement
- Supports mobile printing services such as Sharp Print Service Plugin\*<sup>3</sup> and AirPrint
- Multi-layered security features keep information safe—in the document, on the device, and over the network
- A range of embedded features hardens the device against attacks
- Standard Confidential Print feature helps ensure output security via simple PIN

\*1: Contact a Sharp customer representative for availability and other details.

\*2: The numerical value is for the printer's base unit only.

\*3: Contact a Sharp customer representative for details.



## SPECIFICATIONS

### General

Type	Desktop
Engine speed	A4*1: Max. 40 ppm
Control panel display	2-line LCD
Paper size	Max. A4, min. A6
Paper capacity (75 g/m <sup>2</sup> )	Standard: 350 sheets (250-sheet tray and 100-sheet multipurpose feeder) Maximum: 900 sheets (350 sheets & optional 550-sheet tray)
Paper weight	Trays 1-2: 60 g/m <sup>2</sup> to 120 g/m <sup>2</sup> Multipurpose feeder: 60 g/m <sup>2</sup> to 217 g/m <sup>2</sup>
First print time*2	5.9 sec.
Memory	256 MB
Dimensions (W x D x H)	368 x 363 x 222 mm
Weight (approx.)	9.3 kg

\*1: Short-edge feeding.

\*2: Short-edge feeding off from 1st paper tray, printer in fully ready condition.  
May vary depending on operating conditions and environment.

### Printer

Resolution	2,400 Image Quality, 1,200 Image Quality, 600 x 600 dpi
Interface	USB 2.0 (high-speed), 10Base-T/100Base-TX, wireless LAN (IEEE 802.11 b/g/n)
Supported OS	Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Windows Server 2022, Windows 7, Windows 8.1, Windows 10, Windows 11, Mac OS 10.10 to 10.15, 11, 12, 13, 14
Network protocols	TCP/IP
Printing protocols	LPD, Raw TCP (port 9100), enhanced IP (port 9400), FTP, TFTP, IPP
PDL	PCL 5e/PCL 6 emulation, PostScript 3 emulation
Available fonts	89 fonts for PCL, 158 fonts for PostScript 3 emulation

• Design and specifications are subject to change without prior notice.

• Windows Server and Windows are trademarks of the Microsoft group of companies. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PostScript 3 is either a registered trademark or trademark of Adobe in the US and/or other countries. All other brand names and product names may be trademarks or registered trademarks of their respective owners.

## SYSTEM CONFIGURATION

