

Free to fit—Perfect for your business

High Productivity

- 100-sheet RSPF scans documents at 52 opm*¹ (one-sided)
- Multi bypass tray feeds paper up to 256 g/m² thick
- Print Release function enables printout from any compatible networked MFD*²
- Direct printing of Microsoft Office (docx, xlsx, pptx) files*³ (option)
- OCR allows users to convert scanned documents into editable Office Open XML (docx, xlsx, pptx) files and searchable PDFs (option)
- Multicrop/Image Crop functions simultaneously scan multiple receipts/photos and save them as separate files
- Supports compact PDF (option)
- For large-volume scanned data, a URL can be generated and shared via e-mail
- Inbound routing lets you forward received faxes to a preset destination (option)

Exceptional Ease of Use

- Easy UI mode on 7.0-inch colour LCD touchscreen
- Dedicated user icons allow quick login to personalised operation screen
- Control panel tilts at various angles for easy access
- Red and green LED lamps light up to notify users of machine/job status
- Small footprint*⁴ (568 × 630 mm)
- Energy-saving functions include short warm-up time, power consumption of 0.5 W in fax/network standby, and more

Superb Image Quality

- Genuine Adobe PostScript 3 (option)
- Sharp's proprietary Auto Colour Mode, further improved for enhanced scan performance
- Automatically makes scan settings according to document type—provides optimal scan results

Secure Information Sharing

- Secondary Ethernet port to support additional network*⁵
- Wireless connectivity enables easy access from mobile devices and flexible MFD placement (option)
- NFC*⁶ and QR Code enable easy direct connection between MFD and mobile device
- Supports Sharpdesk Mobile print/scan application and various mobile printing services (option)
- Application Portal offers apps for downloading and installing onto MFD
- Easy access to public cloud services such as OneDrive for Business via single sign-on (option)
- Sends scanned data via Gmail™ or Microsoft Exchange/Online accounts
- Sharp OSA (Open Systems Architecture) allows integration with network and cloud-based applications (option)
- Advanced system/data protection and access control, including firmware self-recovery and whitelisting*⁷

*1: Originals per minute; when feeding A4 sheets.

*2: Contact a Sharp customer representative for details on the recommended maximum number of connectable MFDs.

*3: This function is enabled via Qualcomm® DirectOffice™ technology.

*4: "Footprint" refers to the part directly adjacent to the floor or desk space. The numerical value is for the MFD's base unit only.

*5: Requires third-party Ethernet adaptor that supports two lines.

*6: The NFC interface is for Android™ devices running Android 9 or earlier. Requires third-party NFC card reader.

*7: Certain functions require optional equipment.



SPECIFICATIONS

General		Document Filing	
Type	Desktop	Document filing capacity ^{*13}	Main and custom folders: 5,000 pages or 500 files Quick file folder: 5,000 pages or 500 files
Engine speed	A4 ^{*1} : Max. 25 ppm A3: Max. 14 ppm	Stored jobs ^{*14}	Copy, print, scan, fax
Control panel display	7.0-inch colour LCD touchscreen	Storage folders	Quick file folder, main folder, custom folder (max. 1,000 folders)
Paper size	Max. A3W, min. A6 ^{*2}		
Paper capacity (80 g/m ²)	Standard: 350 sheets (250-sheet tray and 100-sheet multi bypass tray) Maximum: 1,850 sheets (350 sheets & optional 3 x 500-sheet tray)		
Paper weight	Tray 1: 60 g/m ² to 105 g/m ² Trays 2–4 (BP-CS10/DE10): 60 g/m ² to 220 g/m ² Multi bypass tray: 55 g/m ² to 256 g/m ²		
Warm-up time ^{*3}	17 sec. ^{*4}		
Memory	5 GB (copy/print shared) 128 GB SSD ^{*5}		
Power requirements	Rated local AC voltage ±10%, 50/60 Hz		
Power consumption	Max. 1.84 kW (220 V to 240 V)		
Dimensions (W x D x H)	568 x 630 x 653 mm		
Weight (approx.)	54 kg		
Copier		Printer	
Original paper size	Max. A3	Resolution	600 x 600 dpi, 9,600 (equivalent) x 600 dpi
First copy time ^{*6}	Colour: 11.0 sec. B/W: 8.0 sec.	Interface	USB 2.0 (host, high-speed), 10Base-T/100Base-TX/1000Base-T, wireless LAN (IEEE 802.11 b/g/n) ^{*15}
Continuous copy	Max. 9,999 copies	Supported OS ^{*16}	Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Windows Server 2022, Windows 8.1, Windows 10, Windows 11 Mac OS 10.15, 11, 12, 13, 14, 15, 26
Resolution	Scan (colour): 600 x 600 dpi Scan (B/W): 600 x 600 dpi, 600 x 400 dpi Print: 600 x 600 dpi, 9,600 (equivalent) x 600 dpi (depending on copy mode)	Network protocols	TCP/IP
Gradation	Equivalent to 256 levels	Printing protocols	LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, FTP for downloading print files, IPP, SMB, WSD
Zoom range	25% to 400% (25% to 200% using RSPF) in 1% increments	PDL	Standard: PCL 6 emulation Option: Adobe PostScript 3
Preset copy ratios	Metric: 10 ratios (5R/5E), inch: 8 ratios (4R/4E)	Available fonts	80 fonts for PCL, 139 fonts for Adobe PostScript 3
Colour Scanner		Facsimile (requires optional MX-FX15)	
Scan method	Push scan (via control panel) Pull scan (TWAIN-compliant application)	Compression method	MH/MR/MMR/JBIG
Scan speed ^{*7}	Colour & B/W: Max. 52 originals/min.	Communication protocol	Super G3/G3
Resolution	Push scan: 100, 150, 200, 300, 400, 600 dpi Pull scan: 75, 100, 150, 200, 300, 400, 600 dpi 50 dpi to 9,600 dpi via user setting ^{*8}	Transmission time	Less than 3 seconds ^{*17}
File formats	TIFF, PDF, PDF/A-1a ^{*9} , PDF/A-1b, encrypted PDF, XPS, compact PDF ^{*10} , JPEG ^{*11} , searchable PDF ^{*9} , OOXML (pptx, xlsx, docx) ^{*9} , text (TXT [UTF-8]) ^{*9} , rich text (RTF) ^{*9}	Modem speed	33,600 bps to 2,400 bps with automatic fallback
Scan destinations	Scan to e-mail/desktop ^{*12} /FTP server/network folder (SMB)/USB drive/local drive	Transmission resolution	From Standard (203.2 x 97.8 dpi) to Ultra Fine (406.4 x 391 dpi) A3 to A5
		Recording size	A3 to A5
		Memory	1 GB (built-in)
		Greyscale levels	Equivalent to 256 levels

- Design and specifications are subject to change without prior notice.
- Microsoft, OneDrive, Windows, and Windows Server are trademarks of the Microsoft group of companies. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe in the US and/or other countries. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. Gmail and Android are trademarks of Google LLC. Mac is a trademark of Apple Inc., registered in the US and other countries. Qualcomm DirectOffice is a product of

- *1: Long-edge feeding. *2: Only short-edge feeding can be used with A6 paper. *3: In a standard measurement environment. May vary depending on operating conditions and environment.
- *4: When starting the MFD via the power button. 28 seconds when starting via the main power switch.
- *5: SSD capacity depends on procurement and sourcing status. *6: Long-edge feeding of A4 sheets from 1st paper tray, using document glass, MFD in fully ready condition. May vary depending on operating conditions and environment. *7: Based on Sharp's A4 standard chart, using document feeder, long-edge feeding, one-sided scanning, and factory default settings. Scan speed will vary depending on the type of document and the scan settings. *8: Resolution will vary depending on the size of the scanned area. *9: Requires optional MX-EB20L. *10: Requires optional MX-EB19L. *11: Colour/greyscale only. *12: Requires Network Scanner Tool Lite. *13: Storage capacity will vary depending on the type of document and the scan settings. *14: Some features require optional equipment. *15: Requires optional MX-EB18. *16: Mac OS requires optional MX-PK13L. *17: Based on Sharp's standard chart with approx. 700 characters (A4 long-edge feeding) at standard resolution in Super G3 mode, 33,600 bps, JBIG compression.

Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other brand names and product names may be trademarks or registered trademarks of their respective owners.

Qualcomm® DirectOffice™

SYSTEM CONFIGURATION

