

SHARP

E Series
Laser projector ideal for the classroom

E501U



Eliminate lamp replacements with long lasting laser technology

The Sharp E Series LCD, laser projector provides the essential features you need to simply and reliably connect with your audience.

Essential Features for Educational Facilities

- WUXGA resolution and 5,000 lumens brightness allow presenters to leave the lights on and still see the images clearly
- Direct power on and quick power off help maximize presentation time
- Built-in 16-watt speaker provides volume needed for typical classrooms
- Plug and play intuitive setup and operation
- Sufficient connections for multiple sources with dual HDMI inputs

Low Maintenance Environmental Design

- Exceptional laser life with ECO Mode™ technology increases operation up to 20,000 hours, while lowering power consumption
- Power management enables projector to automatically turn off when an incoming signal is not detected from any of the inputs
- Auto power on when a signal is detected
- Quick start (3 to 4 seconds) lets you begin presenting in seconds

Specifications

Ships With

Remote control, batteries, power cord

Ordering Model Numbers

XP-E501U-W



Model	XP-E501U	
Display Technology	0.64" LCD	
Light Output (lumens)	Normal Center	5,000 Lumens 5,300 Lumens
Screen Resolution	WUXGA 1920x1200	
Aspect Ratio	Up to 4K UHD (3840x2160) @ 30Hz via HDMI	
Contrast Ratio (up to)	16:10 (Supports 4:3, 16:9, 21:9)	
Laser Life	3,000,000:1 (Dynamic)	
Screen Size (diagonal)	20,000 hours (until 50% brightness)	
Projection Distance	30-300 in. / 0.762 to 7.6 m	
Lens	Zoom Manual, 1.2x	
Throw Ratio	1.35-1.64:1	
F-number, focal length	F: 1.61-1.76, f: 19.1-23.0 mm	
Keystone Correction	+/- 30° horizontal, +/-30° vertical	
Synchronization Range	Horizontal Vertical	15 to 100KHz 24 to 85Hz
SD/HD Video Signal Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K UHD	
PC Signal Compatibility	VGA, XGA, WXGA, SXGA, UXGA, WUXGA	
Macintosh Compatibility	Yes	
RGB1 (digital)	HDMI w/HDCP (V1.4)	
RGB2 (digital)	HDMI w/HDCP (V1.4)	
Output Terminals	Audio Out	
Wired LAN	Stereo Mini Jack (variable)	
USB	RJ-45 (10BASE-T/100BASE-TX)	
Type A	Power (1.5A)	
Type B	Service	
External Control	RS-232 (D-Sub 9pin), IR, LAN	
Built-in Speaker	16W (mono)	
Power Requirements	100-240V AC, 50/60 Hz	
Input Current	3.3A - 1.4A	
Power Consumption	(Normal/Sleep/Standby)	330W / 5.5W / 0.37W
Installation Orientation	Floor/Front, Floor/Rear, Ceiling/Front, Ceiling/Rear	
Product Dimensions (WxHxD)	390 x 128 x 294 mm	
Net Weight	5.0 kg	
Shipping Dimensions (WxDxH)	492 x 239 x 443 mm	
Gross Weight	8.0 kg	
Fan Noise	36 dB (default) / 29 dB (silent)	
Regulations	CE; ErP; RoHS; RCM; TUEV Type Approved	
Operating	Altitude	0 to 3000 m, >1,700m req High Altitude (fan mode)
	Temperature	0-45°C
	Humidity	20 to 80% (Non-Condensing)
Storage	Altitude	0-12,000m / 0-39,370ft (above sea level)
	Temperature	-10 50°C
	Humidity	10% - 85% (Non-Condensing)

Sharp, NaViSet and all related trademarks are trademarks or registered trademarks of Sharp Corporation and/or its affiliated companies. The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. All other brand names and product names may be trademarks or registered trademarks of their respective owners. Design and specifications are subject to change without prior notice.

www.sharp.net.au

VisualSolutions@sharp.net.au

1300 135 022

SHARP CORPORATION OF AUSTRALIA PTY LTD, P.O. Box 84, Macquarie Park, NSW, 2113: ABN 40 003 039 405

This document is © 2026 Sharp NEC Display Solutions Ltd.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. (January 2026)