

FSI power-tech aps Erhvervsparken 4B DK-7160 Tørring +45 7580 5558 sales@fsi.dk

FSI H40S 50-75

Brochure

Hydraulic Stump Cutter with sweep for 50-75 I/min.

FSI H40S is a stump grinder attachment with an integrated swing movement for loaders and tool carriers.

The recommended machine size is 1.5 - 2.5 t.

The H40S is attached using a tool grip/coupling. The swing movement is performed using two cylinders controlled either from the electronic control box or connected via an existing joystick.

The machine is equipped with a flange to attach the tool grip. Includes hydraulic hoses.



Hydraulic

Power requirement 18-31 kW/25-42 hp

Oil flow 50-75 I/min.
Oil pressure Max 250 bar

Hydraulic connections Pressure/return: 1/2" ISO A Male

Leak oil: 1/2" ISO A Female

Cutting Head

Cutting disc diameter 470 mm

Tooth system 3 x turnable

Tooth diameter 24,5 mm

No of teeth 16
Max. cutting dept 52 mm
Cutting disc drive Direct

Sweep Hydraulic with el-control Working area 1100 mm (2 x 37 degr.)

Un painted baseplate Standard

Operator control

El-box with magnetic base for swepfunction







FSI power-tech aps Erhvervsparken 4B DK-7160 Tørring +45 7580 5558 sales@fsi.dk

FSI H40S 50-75

Brochure

Hydraulic Stump Cutter with sweep for 50-75 l/min.


Measurements

Length1240 mmWidth800 mmHeight650 mmWeight200 kg

Capacity by cutting

Average time for grinding stumps .

ø400 mm: 12 min.ø650 mm: 25 min.ø105 mm: 75 min



All based on figures from users grinding stumps 15 cm high to

15 cm below ground



