

FSI power-tech aps Erhvervsparken 4B DK-7160 Tørring +45 7580 5558 sales@fsi.dk

FSI H40S 80-110

Brochure

Hydraulic Stump Cutter with sweep for 80-110 l/min.

FSI H40S is a stump grinder attachment with an integrated swing movement for loaders and tool carriers.

The recommended machine size is 1.5 - 2.5 t.

The H40S is attached using a tool grip/coupling. The swing movement is performed using two cylinders controlled either from the electronic control box or connected via an existing joystick.

The machine is equipped with a flange to attach the tool grip. Includes hydraulic hoses.



Hydraulic

Power requirement 29-48 kW/40-65 hp
Oil flow 80-110 l/min.
Oil pressure Max 250 bar

Hydraulic connections Pressure/retur : 3/4" ISO A Male

Leak oil: 1/2" ISO A Female

Cutting Head

Cutting disc diameter 470 mm

Tooth system 3 x turnable


Tooth diameter 24,5 mm

No of teeth 16

Max cutting depth 52 mm
Cutting disc drive Direct

Sweep Hydraulic with el-control Working area 1100 mm (2 x 37 degr.)

Un painted baseplate Standard



El-box with magnetic base for swepfunction







FSI power-tech aps Erhvervsparken 4B DK-7160 Tørring +45 7580 5558 sales@fsi.dk

FSI H40S 80-110

Brochure

Hydraulic Stump Cutter with sweep for 80-110 l/min.

Measurements

Length1240 mmWidth800 mmHeight720 mmWeight250 kg


Capacity by cutting

Average time for grinding stumps .

 ø400 mm:
 12 min.

 ø650 mm:
 25 min.

 ø105 mm:
 75 min



All based on figures from users grinding stumps $\,$ 15 cm high to 15 cm below ground

