

FSI power-tech aps Erhvervsparken 4B DK-7160 Tørring +45 7580 5558 sales@fsi.dk

FSI T25

Brochure

Stump Cutter for PTO 25-55 hp

FSI T25 is an ideal attachment for smaller tractors and similar machines with a PTO outlet.

The frame and 3-point linkage (cat. 1) ensure stability during grinding.

All movements are controlled via the joystick, the control box also has an option to adjust the speed of the swing movement. Includes joystick control, PTO shaft and hydraulic top link.



Hydraulic

Tractor power requirement Oil flow Oil pressure Hydraulic connections Hydraulic QR couplings

PTO Speed PTO with freewheel

Cutting Head

Cutting disc diameter Tooth system Tooth diameter No of teeth's Max cutting depth Cutting disc drive Sweep

Cutting dimensions

Hydraulic toplink

Cutting height above ground Cutting depth below ground Cutting sweep width Sweep speed 350 mm 400 mm 1000 mm Adjustable

Included

19-41kW/25-55 hp Max 35 l/min. Max. 150 bar Pressure + return 2 x 1/2"

540 rpm Included

470 mm 3 x turnable 20,5 mm 18 41,5 mm V-belt system Hydraulic sweep



www.fsi.dk



FSI T25

FSI power-tech aps Erhvervsparken 4B DK-7160 Tørring +45 7580 5558 sales@fsi.dk

Brochure

Stump Cutter for PTO 25-55 hp

Operator control

Joystick control

Hydraulic

1750 mm

1000 mm

1100 mm

240 kg

All based on figures from users grinding stumps 15 cm high to

Measurements
Length
Width

Height Weight

Capacity by cutting

15 cm below ground

Average time for grinding stumps .Ø400 mm:8 min.Ø650 mm:15 min.Ø1050 mm:50 min.







www.fsi.dk