

FSI power-tech aps Erhvervsparken 4B DK-7160 Tørring +45 7580 5558 sales@fsi.dk

FSI T27

Brochure

Stump Cutter for pto 35-80 hp

FSI T27 is an attachment for tractors and similar machines with a PTO outlet.

The frame and 3-point linkage (cat. 1/2) ensure stability during grinding.

All movements are controlled via the joystick, the control box also has an option to adjust the speed of the swing movement.

Includes joystick control and PTO shaft.

Hydraulic

Tractor power requirement Oil flow Oil pressure Hydraulic connections Hydraulic QR couplings

PTO Speed PTO with freewheel

Cutting Head

Cutting disc diameter Tooth system Tooth diameter No of teeth's Max cutting depth Cutting disc drive Sweep Extend

Cutting dimensions

Cutting height above ground Cutting depth below ground Cutting sweep width Sweep speed Hydraulic toplink 27-60 kW/35-80 hp Max 35 l/min Max 180 bar Pressure + return 2 x 1/2"

540 rpm Included

470 mm 3 x turnable 24,5 mm 16 43,5 mm V-belt system Hydraulic sweep Hydraulic 300 mm

400 mm 400 mm 1400-1750 mm (extend) Adjustable Included



www.fsi.dk



FSI power-tech aps Erhvervsparken 4B DK-7160 Tørring +45 7580 5558 sales@fsi.dk

FSI T27

Brochure

Stump Cutter for pto 35-80 hp

Operator control

Joystick control

Electro hydraulic

Measurements	
Length	2000 mm
Width	1350 mm
Height	1200 mm
Weight	360 kg

Capacity by cutting

Average time for grinding stumps .Ø400 mm:6 min.Ø650 mm:12 min.Ø1050 mm:35 min.

All based on figures from users grinding stumps 15 cm high to 15 cm below ground





www.fsi.dk