

Stump cutter FSI B22

FSI power-tech aps Erhvervsparken 14 DK-7160 Tørring +45 7580 5558 mail: sales@fsi.dk

Compact • Hydraulic 2WD • Turntable design • 14 hp Kohler Petrol

FSI B22

Self-propelled stump cutter

Self propelled means the user can mowe the machine with ease, both mowing to the stump and espacially when mowing the machine onto a trailer or lorry after use.

The turntable design uses a povot joint between the stump grinder and the wheel axle ensures easy and smooth grinding even under difficult conditions.

Standard on FSI B22

- Large wheels with hydraulic 2WD
- •Independent wheel brakes
- •Engine with electric start
- Electro-magnetic clutch
- Valve for free run on the wheels
- Manuel sweep via pivot joint
- V-belt drive for optimal capacity with a minimum of power loss
- •3 x turnable tooth-system with FSI Holders
- Special designed cutting disc for optimal capacity and durability
- Vibration damped handle
- Adjustable handle
- Integrated points for lashing
- •Lifting points for handling with crane
- •Safety. If the operator leaves the handle the cutting wheel will automatically stop
- Tool set for wearing parts

Options

- •Hour meter with alarm 25h (lube) and 100h (oil)
- Manual box

Capacity by cutting

Time spent for cutting stumps with diameter:

ø400 mm = 12 min.

ø650 mm = 25 min.

ø1050 mm = 90 min.

All based on experience by grinding stumps 15 cm high to 15 cm below ground.









Stump cutter FSI B22

FSI power-tech aps Erhvervsparken 14 DK-7160 Tørring +45 7580 5558 mail: sales@fsi.dk

Compact • Hydraulic 2WD • Turntable design • 14 hp Kohler Petrol

Engine

Engine size 10,5 kW/14 Hp Engine type Kohler ECH440

Fuel Petrol
Fuel tank 7,0 liter
Hours per tank App. 3. hours

Cutting head

Cutting disc diameter 370 mm

Tooth system 3 x turnable

Tooth diameter 20,5 mm

No of teeth 8

Max cutting depth 24,5 mm

Clutch Electro magnetic

Cutting disc drive V-belts Sweep Manual

Wheels/Brakes

Wheels Ø410 x 110

Brakes One for each wheel
Transmission 2 x hydraulic motor
Speed Up to 3 km/h

Cutting dimensions

Cutting height above ground 300 mm
Cutting depth below ground 250 mm
Cutting sweep width 900 mm
Sweep speed Manual

Operator control

Control panel In the handle

General dimensions

Length1740 mmWidth680 mmHeight1250 mmWeight210 kg





