

THE 30 SERIES

TTR 3800 | 4800



25,7_{hp}

38,7_{hp}

ACTIO



10 THE RANGE

RGS



*4800



OPT

HYDROSTATIC TRANSMISSION

EXG
MAXIMUM
PROTECTION
GUARANTEE

5
STAGE



Frame	ACTIO™ integral oscillating frame • RGS™ reversible drive system • Steering wheels - Four equal-size driving wheels	
Engine type	3800 F YANMAR - Direct injection diesel Stage 5 - 3 Cylinders - 1331 CC Power 18.9 kW / 25.7 hp - 2800 rpm Max torque 86.8 Nm at 1300 rpm	4800 F YANMAR - Supercharged direct injection diesel - Stage 5 - 3 Cylinders - 1568 CC Power 28.5 kW / 38.7 hp - 2600 rpm Max torque 126 Nm at 1690 rpm
Transmission	Hydrostatic with hydraulic control	
Power take-off	Rear, independent 2-speed 540 and 1000 rpm	
Hydraulic system	Standard hydraulic system comprised of: 3 rear double-acting remote valves with float position (total of 6 rear quick couplers)	
Rear power lift	Hydraulic lift with 3-point linkage Lifting capacity (kg): 910 Fixed lift arms with Cat. 1-1N ball ends with spring clips; Cat. B rear tow hook; Front tow hook	
Brakes	Hydraulic service brake, pedal operated, acting on the rear wheels. (opt. on all wheels) - Mechanical parking brake, lever operated, acting on the rear wheels.	
Weight	With roll bar: 1150 to 1200 kg	

DIMENSIONS WITH STANDARD WHEELS: 7.50-16

	A	B	C	D	-	F	G	H	I	L
3800	2970 to 3065	945	1360	665 to 760	-	2060	240	-	-	1175
4800	-	-	-	-	-	-	-	-	-	-

