

BP-20C25/20C20

A3 Colour MFDs



Simplicity³

Make everyday tasks much easier. And do it all with a lot more style!

With these new generation, entry-level A3 colour MFDs you can rediscover simplicity. By thinking outside the box, we've designed a new type of product to deliver essential business functionality.

If you want to print, copy, scan or fax*1 documents they get the job done quickly and easily – even from mobile devices. And their compact design adds a real touch of style to any office.

Simply more stylish

Why be ordinary, when you can be extraordinary. These MFDs have a unique cubic design with a distinctive two-tone colour scheme. And they are one of the smallest A3 colour devices available – measuring just $56 \times 56 \times 65.3$ cm. So they can fit in almost anywhere and enhance the look of your workspace, making them an ideal choice for use on office desktops or in locations with restricted space.

They are simple to use, simple to manage and simply more stylish – it's simplicity³.

Simple to use

There's no complex set-up or messy cables. An optional wireless LAN lets you connect to any WiFi enabled device, so that anyone can print or scan directly from their smartphone, tablet or PC using Airprint™*, Android™ printing framework* or the Sharpdesk Mobile app. Or insert a USB drive and simply select a file from the pop-up menu to directly print any stored documents or save scans to it without having to use a PC.

*1 Requires optional MX-PK11 PS3 Expansion Kit.



A stylish complement to any office space.



These MFDs are equipped with a range of features to ensure you can work more efficiently and with the minimum of fuss. A tiltable 4", 5-line LCD control panel lets you easily view and control the various settings and options. Pop-up messages will also appear when you add various media to the bypass tray to help you quickly select paper type and size settings.

To save time and effort when you're copying documents, they automatically rotate and sort multi-page documents into sets or let you copy the front and back of ID cards onto one page. Digitising and sharing information is also quick and simple, as you can scan and send documents in full colour.

Simple to manage

In addition, the MFDs are really easy to manage. You can check the machine and job status at a glance, even from a distance, thanks to the status indicator lamps. And they automatically enter an energy saving mode if they've been inactive for a while, so you save money.

Simply safer

Just because these MFDs are really simple to use, it doesn't mean that your sensitive business information is at risk. Like all of our MFDs, they include a range of security features designed to protect your documents:

- **User authentication** prevents any unauthorised access by requiring a password to be entered
- Device authentication restricts access to devices whose IP/MAC address is pre-registered
- Advanced network encryption keeps your information secure across the network using IPsec and SSL protocols



^{*1} Requires optional BP-FX10, Fax Expansion Kit.

 $^{^{\}star_2}$ Requires optional MX-EB18, Wireless LAN Adapter.

Specifications

General		
Engine speed (ppm/cpm) (Max)	A4*1	А3
BP-20C25	25	14
BP-20C20	20	12
Control panel display	4-inch 5-line	mono LCD with hard key
Paper size (Min – Max)	A6*2 - A3W	
Paper weight (g/m²)		
Drawer 1	60 - 105	
Drawers 2 - 4	60 - 220	
Multi-bypass	55 - 256	
Paper capacity (Std – Max)		
Sheets	350 - 1,850	
Drawers	1 - 4 (plus bypass tray)	
Warm-up time ^{⋆3} (seconds)	29*4	
Memory (GB)		
Copier/Printer (shared)	2	
Power requirements	Rated local	AC voltage ±10%, 50/60 Hz
Power consumption (kW) (Max)	1.84 (220 to	240V)
Dimensions (mm) (W x D x H)	560 x 560 x 6	53

-	-:-:	ı
L O	niei	Г
	p.c.	

Weight (kg) (approx.)

Copier			
Original paper size (Max)	А3		
First copy time*5 (seconds)	Colour 11.5	B/W 8.0	
Continuous copies (Max)	999		
Print resolution (dpi)			
Scan	600 x 600, 600 x 400		
Print	600 x 600		
Gradation levels	256		
Preset copy ratios (Metric)	10 ratios (5R/	5E)	

Network Printer

600 x 600
USB 2.0, 10Base-T/100Base-TX/1000Base-T
Standard: Windows Server® 2008, 2008R2, 2012, 2012R2, 2016, 2019, Windows® 7, 8.1, 10 Optional *6: Mac OS 10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13, 10.14 & 10.15
TCP/IP
LPR, Raw TCP (port 9100), FTP for downloading print files, IPP, SMB, WSD
Standard: PCL 6 Optional: PostScript® 3™ emulation
80 fonts for PCL, 136 fonts for PostScript® 3™ *6

Network Scanner

Scan method	Push scan (via control panel) Pull scan (TWAIN-compliant application)	
Scan speed *7 (ipm) BP-20C25/BP-20C20	One-sided 37	Two-sided 15
Resolution (dpi) (Max) Push scan Pull scan	100, 150, 200, 3 75, 100, 150, 20 50 to 9,600 dpi	
File formats	TIFF, PDF, JPEG*9	
Scan destinations	Scan to e-mail, desktop*10, FTP server, network folder (SMB), USB memory	
Scanner utilities	Network Scanner Tool Lite	


Fax (optional BP-FX10 required)

- un (optional Br. 17120 regained)	
Compression method	MH/MR/MMR/JBIG
Communication protocol	Super G3
Transmission time ^{★11} (seconds)	2
Modem speed (bps)	33,600 – 2,400 with automatic fallback
Recording width	A5 - A3
Memory (MB)	64

Wireless LAN (optional MX-EB18 required)

Compliant regulation	IEEE802.11n/g/b
Access mode	Infrastructure mode, Software AP mode
Security	WEP, WPA/WPA2-mixed PSK, WPA/WPA2-mixed EAP*12, WPA2 PSK, WPA2 EAP*12

Configurations















*¹ Long-edge feeding, *² Only short-edge feeding can be used with A6 paper, *³ In a standard measurement environment. May vary depending on operating conditions and environment. *⁴ When starting via the main power switch.
** Long-edge feeding of A4 sheets from 1st paper tray, using document glass, MFD in fully ready condition. May vary depending on operating conditions and environment. *6 Requires optional MX-PK11. *¹ Scan speeds measured in accordance with IsO/IEC 24735:2009 standard for devices equipped with an automatic document feeder only. Scan speed will vary depending on the type of document the scan settings, operating conditions and environment. Based on Sharp's A standard chart, using document feeder, long-one-sided scanning and factor year. *Resolution will vary depending on the size of the scanned area. *Colour/greyscale only. **Dequires Network Scanner Tool Lite. *¹¹ Based on Sharp's Standard chart with approx. 700 characters (A4 short-edge feeding) at standard resolution in Super G3 mode, 33,600 bps, JBIG compression. *¹² Not applicable to Software AP Mode.

Design and specifications are subject to change without prior notice. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AReader and the AReader logo are registered trademarks of Tokyo Shoseki Co., Ltd. IOS is a trademark or registered trademark of Cisco Systems, Inc. in the US and other countries and is used under license by Apple Inc. Android is a trademark of Google LLC. Windows and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Mac is a trademark of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett-Packard Company. PostScript 3 is either a registered trademark or trademark of Adobe Systems Incorporated in the US and/or other countries. All other brand names and product names may be trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&OE.



Distributed by:

SHARP CORPORATION OF AUSTRALIA PTY LTD

ABN 40 003 039 405

P.O. Box 84, Macquarie Park, NSW, 2113

Tel: (02) 9830 4600 www.sharp.net.au

©SHARP CORPORATION (SEPTEMBER 2020)