

Datasheet





Functionality you need, at the price you want

A professional solution for low-budget applications, the E series forestalls the lure of domestic TVs which are not fit-for-purpose. Designed for the rigours of commercial usage, the E Series delivers the functionality and reliability you need, at the price you want.

An integrated MediaPlayer supports native UHD resolution and High Dynamic Range (HDR) for deep contrasts and natural looking content playback with auto-play function. Requiring no additional cables, external devices or signage software, the USB MediaPlayer enables a simple seamless professional signage solution. Meanwhile, a 10W USB interface supports connection of external devices should additional computing power be required.

For instant start-up in meeting spaces, inputs are detected automatically with easy switching between HDMI sources. Facilities managers will welcome the ability to remotely control their digital estate via the network thanks to the integrated LAN and NEC's NaviSet Administrator 2 functionality making the E Series the perfect choice for corporate meeting rooms and entry level digital signage.

Benefits

Slim Design and Integrated Speakers - the aesthetic design is pleasing to the eye and enables easy, low cost installation.

Effortless content playback - the integrated USB media player supports various image video file formats for effortless and standalone content playback.

Future Ready Connectivity – featuring multiple industry standard digital and analogue signal inputs for flexible integration into AV infrastructures.

Professional integration – enriched with essential RS232 functionality, IR and button lock out as well as digital audio output S/ PDIF, the display can easily be integrated into professional applications in public environments.

Standalone operation – the display is designed for straightforward standalone operation due to integrated USB media player, speakers and scheduling functionality.

Product Information

Product Name	NEC MultiSync [®] E438	
Product Group	LCD 43" Essential Large Format Display	
Order Code	E438	

Display

Panel Technology	IPS with Direct LED backlights	
Active Screen Area (W x H) [mm]	941 x 529	
Screen Size [inch/cm]	42.5 / 108	
Aspect Ratio	16:9	
Pixel Pitch [mm]	0.245	
Brightness [cd/m²]	350	
Contrast Ratio (typ.)	1200:1	
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)	
Colour Depth [bn]	1.073 (10bit)	
Response Time (typ.) [ms]	8	
Panel Refresh Rate [Hz]	60	
Haze Level [%]	Standard (1)	
Supported Orientation	Landscape and Portrait	

Synchronisation Rate

Horizontal Frequency [kHz]	15 - 136
Vertical Frequency [Hz]	24 - 75

Resolution

Native Resolution	3840 x 2160				
Supported Resolutions	4096 x 2160;	1920 x 1200;	1280 x 720;	720 x 480;	
	3840 x 2160;	1920 x 1080;	720 x 576;	640 x 480	

Connectivity

Input Video Analogue1 x VGA; Component (RCA); Composite (RCA)Input Video Digital3 x HDMIInput Audio Analogue1 x 3,5 mm jackInput Audio Digital3 x HDMIInput ControlLAN 100Mbit; RS232Input Data1 x USB 2.0 (MediaPlayer); 1 x USB Typ-C (5V/3A, power for external devices)Output Audio Digital1 x SPDIFRemote ControlRemote Control IR; RS-232C (9-pin D-sub) Input			
Input Audio Analogue1 x 3,5 mm jackInput Audio Digital3 x HDMIInput ControlLAN 100Mbit; RS232Input Data1 x USB 2.0 (MediaPlayer); 1 x USB Typ-C (5V/3A, power for external devices)Output Audio Analogue1 x 3,5 mm jackOutput Audio Digital1 x SPDIF	Input Video Analogue	1 x VGA; Component (RCA); Composite (RCA)	
Input Audio Digital3 × HDMIInput ControlLAN 100Mbit; RS232Input Data1 × USB 2.0 (MediaPlayer); 1 × USB Typ-C (5V/3A, power for external devices)Output Audio Analogue1 × 3,5 mm jackOutput Audio Digital1 × SPDIF	Input Video Digital	3 x HDMI	
Input Control LAN 100Mbit; RS232 Input Data 1 x USB 2.0 (MediaPlayer); 1 x USB Typ-C (5V/3A, power for external devices) Output Audio Analogue 1 x 3,5 mm jack Output Audio Digital 1 x SPDIF	Input Audio Analogue	1 x 3,5 mm jack	
Input Data1 x USB 2.0 (MediaPlayer); 1 x USB Typ-C (5V/3A, power for external devices)Output Audio Analogue1 x 3,5 mm jackOutput Audio Digital1 x SPDIF	Input Audio Digital	3 x HDMI	
Output Audio Analogue 1 x 3,5 mm jack Output Audio Digital 1 x SPDIF	Input Control	LAN 100Mbit; RS232	
Output Audio Digital 1 x SPDIF	Input Data	1 x USB 2.0 (MediaPlayer); 1 x USB Typ-C (5V/3A, power for external devices)	
	Output Audio Analogue	1 x 3,5 mm jack	
Remote Control Remote Control IR; RS-232C (9-pin D-sub) Input	Output Audio Digital	1 x SPDIF	
	Remote Control	Remote Control IR; RS-232C (9-pin D-sub) Input	

Sensors

Ambient Light Sensor	Integrated, triggered actions programmable
Temperature Sensor	Integrated, 1 sensors, triggered actions programmable

Electrical

Power Consumption Eco/max. [W]	72 shipping
Power Savings Mode [W]	< 0.5; < 2 (Networked Standby)

Environmental Conditions

Operating Temperature [°C]	+0 to +40
Operating Humidity [%]	10 to 80
Storage Humidity [%]	5 to 85
Storage Temperature [°C]	-10 to +60

Mechanical

Dimensions (W x H x D) [mm]	Without stand: 970.2 x 559.8 x 71	
Weight [kg]	Without stand: 8.9	
Bezel Width [mm]	12.5 (left, right and top); 13.9 (bottom)	
VESA Mounting [mm]	4 holes; 400 x 200 (FDMI); M6	

MediaPlayer

Supported File Storage / File System	USB 2.0 / FAT16, FAT32		
Supported Image Formats	JPG (baseline, progressive, RGB, CMYK); max. resolution 15360 x 8640		
Supported Video Formats	MPG (MPEG1/2/4, max res 1080p@30Hz); MP4 (MPEG2/4, H.263, H.264, HEVC/H.265, max res 3840x2160@60Hz); TS (MPEG2, H.264, HEVC/H.265, max res 3840x2160@60Hz); audio: LPCM, MP3, AAC; WMV (video H.264, Windows Media Video 9, max res 1080p@30Hz, audio WMA 9, WMA 10 Pro)		
Supported Audio Formats	MP3 (MP3); max. bit-rate 320 kBit/s		

Available Options

Accessories	Feet (ST-32E2)	

Features

Energy Efficiency	Energy consumption: 55 kWh/1000 h; Energy efficiency class: G; LED backlight	
Ecological Materials	Manuals on CD	
Ecological Standards	EnergyStar 8.0	

Additional Features

Special Characteristics	Ambient Light Sensor; Audio settings with equalizer; CEC Support; Colour temperature mode; Display Browser Control; Energy saving picture mode; HDMI with UHD at 60 Hz; HDR Gamma Support (HLG, PQ); Mac and Windows compatible; NaViSet Administrator 2; Retail picture mode; Scheduler; SNMP Support; USB Media Player
Colour Versions	Black Front Bezel, Black Back Cabinet
Safety and Ergonomics	EMC Class B; Energy Star 8; FCC; PSB; RCM; TÜV S; UL/C-UL; VCCI
Audio	Integrated Speakers (10 W + 10 W)
Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
Warranty	3 years warranty incl. backlight
Operating Hours	16/7





RCM

VCCI

For more information:

www.sharp.net.au



VisualSolutions@sharp.net.au



SHARP CORPORATION OF AUSTRALIA PTY LTD, P.O. Box 84, Macquarie Park, NSW, 2113: ABN 40 003 039 405

This document is © 2024 Sharp NEC Display Solutions Ltd.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. (Feb 2024)