

### LED-PV012i-220

Indoor LED 1.2mm 220" UHD Bundle

# Product Information Sheet Indoor LED 1.2mm – PRO VESA – 220" UHD Bundle

# LED-PV012i-220





### Essential bundles of brilliance

For bezel-free viewing experiences using vivid LED technology, Sharp's PRO-VESA Series delivers essential visualization for scalable large digital surfaces. Even for cost-conscious deployments for presentation and signage, PRO-VESA provides long lasting Sharp quality with an innovative VESA-mount-compatible form factor of 55" diagonal, and available in off-the-shelf bundle solutions delivering safe operation with minimised downtimes.

Sharp's innovative VESA mount compatible PRO-VESA SMD series generates crisp, clear viewing without fading or distortion in any ambient light, whether it's day or night, bright or dark.

Either free standing or for seamless integration into interiors, the slim design is sleek and chic as befits the latest innovation in digital content delivery. Benefit from excellent viewing angles, consistent vibrant colours, superb brightness and long lasting performance for meeting rooms and signage applications.

## **Benefits**

**Care-free installation** – VESA 400 compatible bundled solutions that deliver all you need to get your LED video wall up and running.

**Large scale for perfectly detailed imagery** – completely bezel-less design with high contrast rates deliver an unhinderedviewing experience.

**Slim design** – with a flush rear profile, LED modules can be integrated very close to the wall with no gap necessary due to minimal heat emission.

Front serviceable modules – with front access to the LED modules, maintenance is easy.

Visual excellence – high contrast and high brightness is inherent in LED delivery, benefit from Sharp's long-lasting quality.

sharp.net.au

| Product information             |   |
|---------------------------------|---|
| Product Name                    | LED-PV012i-220 UHD Bundle   |
| Product Group                   | Indoor LED, PRO-VESA series   |
| Order Code                      | LED-PV012i-220  |
| Display                         |   |
| Pixel Configuration             | 3-in-1 SMD (Black)  |
| LED type                        | SMD (1010)  |
| Screen Size [inch/cm]           | 220 / 559   |
| Aspect Ratio                    | 16:9  |
| Pixel Pitch [mm]                | 1.263   |
| Brightness (max.) [cd/m²]       | 800   |
| Lifetime                        | 100,000 hrs (50% brightness)  |
| Contrast Ratio (typ.)           | 6000:1  |
| Viewing Angle [°]               | 160 horizontal / 160 vertical   |
| Dimming Capability              | 256 levels  |
| Colour Processing               | 16 bit  |
| Colours                         | 281 trillion  |
| LED Driving Method              | 1/27 dynamic scan   |
| Frame Rate                      | 50/60 Hz  |
| Refresh Rate [Hz]               | < 3840  |
| Colour Temperature [K]          | 2500 - 10000  |
| Screen Resolution               |   |
| Resolution                      | 3840 x 2160   |
| Resolution per m <sup>2</sup>   | 627,159   |
| Number of Pixel per module[dot] | 240 x 270   |
| Number of Pixel per card[dot]   | 259,200   |
| Connectivity                    |   |
| Input Video Digital             | 1x HDMI 2.0; 2x 3G-SDI; 4x DVI-D (as standard, alternative options available) |
| Input Control                   | 1x Ethernet LAN; 1x USB IN; 1x USB OUT (Cascading)                            |
| -                               |   |
| Electrical                      |   |
| Total Power Consumption [W]     | 2,112 typ. / 5,680 max.   |
| Power Consumption typ. [W]      | 160 per m² (normal use)   |
| Power Consumption max. [W]      | 430 per m <sup>2</sup>  |
| Environmental Conditions        |   |
| Operating Temperature [°C]      | -10 to 60   |
| Operating Humidity [%]          | 10 to 90  |
| -10                             |   |

#### Mechanical

| Dimensions (W x H x D) [mm]    | 4,848 x 2,728 x 58 |
|--------------------------------|--------------------|
| Dimensions (W x H x D) [mm]per | 303 x 341 x 8      |
| module                         |                    |
| Weight [kg]                    | 240                |

#### **Additional Features**

| Shipping Content | 1x LED Controller; LED Modules [16x Cabinets, Pixel Cards); Wall mount Kit (4x4); Pixel Card Removal |
|------------------|--|
|                  | Tool; Spare Parts Kit (5% as standard)   |
| Manufacturer     | Sharp  |
| Serviceability   | Front Service  |
| IP Level         | IP40   |
| Certifications   | CCC; CE; ETL; FCC Class B; RoHS; RCM   |
| Warranty         | 3 years conditional warranty   |

# For more information:







1300 135 022

SHARP CORPORATION OF AUSTRALIA PTY LTD, P.O. Box 84, Macquarie Park, NSW, 2113: ABN 40 003 039 405

This document is © 2024 Sharp Corporation of Australia

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. (5<sup>th</sup> Apr 2024)