

Sharp MultiSync® PN-ME982 LCD 98" Message Essential Large Format Display

Preliminary Datasheet



Class-leading performance and value

For best-in-class visual performance and value, the second generation ME series commands featurerich professional capabilities for meeting rooms and signage applications. The multi-functional Sharp MultiSync® displays with high haze panel, native USB-C connectivity, and quick input detection appeals to Enterprise users for Bring Your Own Device simplicity, supporting hybrid workflows and spontaneous meetings.

An integrated System on Chip (SoC) with Android 13 CTS-compliant Operating System brings the most up to date features and security, powering signage applications and commanding high compatibility with CMS partners, making the multi-purpose Sharp MultiSync® ME series suitable for cost sensitive retail signage applications. Experience seamless access to Android apps and install apps directly on the display using the integrated browser, without the hassle and expense of an additional external media player.

Trusted long-life reliability is assured through Japanese engineering standards and high-quality components. The Sharp MultiSync® ME series is a class-leading solution for today's workplace challenges, bringing value and professional performance, without compromise.

Benefits

Seamless connectivity - native USB-C supports Bring Your Own Device workflows, safeguarding

inclusion and boosting productivity, with a single cable connection between notebook and display.

Best readability – aiding high productivity in well-lit meeting spaces, a high haze filter eliminates glare and reflections from windows and other light sources.

Quick input detection – removing potential frustration and smoothing the way to productive meeting outcomes, the display responds immediately when a device is connected.

Third-party compatibility – a flexible signage platform that supports integration with a wide range of workplace and content management systems.

New feature-ready – regular OTA Android OS updates ensure availability of the latest features and system security.

Product Information

Product Name	Sharp MultiSync [®] PN-ME982
Model	PN-ME982
Product Group	LCD 98" Message Essential Large Format Display
Order Code	PN-ME982

Display

Panel Technology	IPS with Direct LED backlights
Screen Size [inch/cm]	98 / 247.7
Aspect Ratio	16:9
Brightness [cd/m²]	450
Contrast Ratio (typ.)	1200:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (8bit + FRC)
HDR	HDR10; HLG; PQ
Response Time (typ.)	8
[ms]	
Panel Refresh Rate [Hz]	60
Haze Level [%]	Pro (25)
Supported Orientation	Landscape; Portrait

Resolution

Native Resolution	3840 x 2160			
Supported Resolutions	1024 x 768;	1360 x 768;	1920 x 1080;	720 x 480;
	1024 x 768;	1366 x 768;	1920 x 1200;	720 x 576;
	1280 x 1024;	1400 x 1050;	1920 x 2160;	800 x 600
	1280 x 1024;	1440 x 900;	3840 x 2160;	
	1280 x 720;	1600 x 1200;	4096 x 2160;	
	1280 x 800;	1680 x 1050;	640 x 480;	

Synchronisation Rate

Horizontal Frequency [kHz]	15 - 135
Vertical Frequency [Hz]	23 - 76

Connectivity

Input Video Digital	$1 \times \text{USB-C}$ (with HDCP 1.3/2.2); $3 \times \text{HDMI}$ (with HDCP)
Input Audio Digital	1x USB-C; 3 x HDMI
Input Control	LAN 100Mbit; remote control wire (3,5mm jack); RS232
Input Data	3 x USB 2.0 (Downstream)

Output Audio Analogue	1 x 3,5 mm jack
Input Detect	Custom; First; Last

Electrical

Power Consumption [W]	206 shipping
Power Savings Mode [W]	< 0.5; < 2 (Networked Standby)
Power Supply	100-240 V AC; 50/60 Hz; internal

Environmental Conditions

Operating Temperature [°C]	+0 to +40
Operating Humidity [%]	20 to 80
Storage Humidity [%]	10 to 90
Storage Temperature [°C]	-20 to 60

Mechanical

Dimensions (W x H x D) [mm]	2,199 x 1,255 x 69
Weight [kg]	54.5
Bezel Width [mm]	18
VESA Mounting [mm]	4 holes; 800 x 600 (FDMI); M8
Ingress Protection	IP5x (front); IP5x (back)
Packaging Dimensions (W x H x D) [mm]	2,360 x 1,425 x 280
Packaging Weight [kg]	82
Colour Bezel	Pantone (Process Black M)
Material	Metal

MediaPlayer

Supported File Storage / File System	FAT16 / FAT32 @ USB 2.0
Supported Video Formats	MKV (Mpeg1/2/3 Layer1/2/3, max res 4096x2160@60fps); MP4 (Mpeg1/2 Layer1/2/3, H.264, HEVC/H.265, max res 4096x2160@60fps)
Supported Audio Formats	.mp3 max. Bit Rate 320 kbps

Embedded Computing

System Version	Android 13
System Memory	4G RAM
Internal Storage	32GB ROM
Built-in Applications	File Manager; Web Browser

Available Options

Accessories	Presence Sensor (KT-RC3); Soundbar (PN-ZCMS1)	

Regulatory

Safety and Ergonomics	BSMI; CE; EMC Class B; Energy Star 8; FCC Class B; KC/KCC; PSB; RCM; RoHS; VCCI
Pixel Failure Class	ISO 9241-307, Class 1
Resistance to Fire	Metal backcover, plastic material certified acc. to UL94-5VB

Green Features

Energy Efficiency	Energy consumption: (TBD) kWh/(TBD) h; Energy efficiency class: G; LED backlight
Ecological Standards	EnergyStar 8.0

3rd Party Certifications

Crestron	Certified for Crestron CCV2 and XiO Cloud

Additional Features

Special Characteristics	DICOM Simulation; HDMI ARC; Powered USB Port (15 W); Removable Logo
Audio	Integrated Speakers (10 W + 10 W)
Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
Warranty	3 years warranty incl. backlight
Operating Hours	18/7
External Control	AMX NetLinx Support; ASCII Control Commands; Crestron Connected; HDMI CEC; Scheduled Timer
Remote Management	Automated Email Alerts; NEC NaViSet Administrator 2
Security	Disable HW Buttons; Disable IR Functionality



For more information:

www.sharp.net.au

VisualSolutions@sharp.net.au

1300 135 022

SHARP CORPORATION OF AUSTRALIA PTY LTD, P.O. Box 84, Macquarie Park, NSW, 2113: ABN 40 003 039 405

This document is © 2025 Sharp NEC Display Solutions Ltd.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. (Feb 2025)