BASINS

Wash Basin Knee Operated - Type 3

Model: SPPL.WB.KO3.xxx

- SPPL = Stoddart Plumbing Product
- WB = Wash Basin
- KO3 = Knee operated, with lower plumbing shroud wall spout
- xxx = TV = Tempering valve
 - =TMVE = Thermostatic mixing valve

eg.: for specification and ordering quote Code: SPPL.WB.KO3.TV



Specifications:

Construction:	304 grade stainless steel construction, Knee operated valve and spout are pre-plumbed.
Water Connection:	 15mm, ½" BSP. For addition of optional TV or TMVE, hot and cold supplies are required. Component claimed temperature control; Thermostatic Mixing Valve = +/- 2 deg C Tempering Valve = +/- 3 deg C Additional water strainer/filter to protect valves from water-borne dirt and scale is fitted as standard.
Waste Connection:	40mm PVC waste supplied (Trap by others)
Unit Fixing:	Unit is supplied with wall mounting bracket with 10mm fixing holes. Optional TV or TMVE is supplied as a loose kit part for plumber to install in compliance with regulations.
Fixing Height:	The unit should be mounted at 800 – 830mm above finished floor level for disabled user access

Model No.	L x D x H (mm)
SPPL.WB.KO3.xxx	560 x 469 x 800




Due to continuous product research and development, the information contained herein is subject to change without notice. Revision: C - 11/06/2021

www.stoddart.com.au www.stoddart.co.nz

Features and Benefits:

- Meets the requirements for hand washing in food premises as detailed in AS4674:2004 (4.4)
- Hygienic hands free use with knee operated front panel
- Timed flow valve provides effective hand washing and saves water
- Includes hygienic, aerated, WELS rated high rise spout for easy access and minimal splash
- Integrated splashback, spout and shroud enclose plumbing for maximum hygiene
- Optional tempering valve and thermostatic mixing valve can be supplied, loose
- Easy mount stainless steel bracket has multiple fixing holes for quick installation by plumber
- Complies with AS 1428.1-2001 for disabled access



Plan View

