URINALS

Slab Step Urinal

Model: SPPL.UR.S.xxxx.yy

SPPL = Stoddart Plumbing Product

UR = Urinal S = Slab

xxxx = Length of urinal yy = T - top water entry = R - rear water entry

= R - right waste = L - left waste

eg.: for specification and ordering quote

Code: SPPL.UR.S.1800.RR

*L & U shaped configurations available.




Features and Benefits:


- Compressed fibre-cement backing for strength and superior noise suppression
- Top or rear water entry
- Concealed sparge spreader for full face waterfall flush
- All internal corners to 25mm radius
- · Custom lengths available




L/H Waste Shown R/H Waste Available

Plan View





Front View



Section A-A

Specifications:

Construction: Fully welded 1.2mm thick 304 stainless steel

construction, no.4 satin finish. Fibre-cement

reinforced backing.

Water Connection: Top entries in ø25 and ø38 dia. Rear entry in

25mm pressure pipe. Custom inlet positions available. Designed for WELS approved flush

devices.

Waste Connection: 50mm to 100mm dropper outlets available

Custom waste positions available.



Due to continuous product research and development, the information contained herein is subject to change without notice.

Revision: A -14/05/2021

www.stoddart.com.au www.stoddart.co.nz

Sold Separately

Flushing Device Options:





FD.CI.PC

FD.EUFS.MIC







