

**CPG746T** 



## **General Drawing:**





Due to continuous product research and development, the information contained herein is subject to change without notice Revision: 01 - 25/01/2022 - A

# Product Information:

- Class leading, European style, professional quality and reliability since 1963
- 700 series, gas 2 x 26 litre, double tank pasta cooker (72 MJ/h)
- Piezo ignition burners with flame failure device and pilot burner
- Burners positioned external to the tank for ease of cleaning inside
- Temperature regulation via variable power flame control
- Low-water level safety switch to prevent operation
  when empty
- Manual water fill via integrated tap and spout with water drainage via concealed ball valve inside the base
- 316 grade stainless steel tanks (2x 340x310mm) for corrosion resistance
- Robust 304 grade stainless steel construction with rounded corners for improved cleaning
- Pressed top work surface with raised edges to protect from overflow
- Enclosed base with front access doors
- Height adjustable stainless steel feet for a 900mm working height
- Baskets and lids not included, sold separately (see below)
- 24-month warranty

#### **Specifications:**

| Model                            | CPG746T          |               |
|----------------------------------|------------------|---------------|
| W x D x H (mm)                   | 800 x 720 x 1054 |               |
| Weight                           | 80kg             |               |
| Oil Capacity                     | 2 x 26L          |               |
| Packed Dimensions (mm)           | 845 x 825 x 1200 |               |
| Packed Weight (mm)               | 90kg             |               |
|                                  | Natural          | Universal LPG |
| Gas Connection                   | 1/2" BSP         | 1/2" BSP      |
| Minimum Normal Test Gas Pressure | 1.3 kPa          | 2.75 kPa      |
| Maximum Normal Test Gas Pressure | 3.5 kPa          | 3.5 kPa       |
| Nominal Test Point Pressure      | 1.0 kPa          | 2.65 kPa      |
| Total Nominal Gas Consumption    | 72 MJ/h          | 72 MJ/h       |

**Note:** It is the responsibility of the installing gas plumber to ensure correct supply and connection sustaining appropriate pressure, when all installed gas appliances are operating at maximum.

### Legend:

- A Gas Connection
- B Drain Connection 1" BSP
- C Cold Water Connection 1/2" BSP

#### Accessories - Sold Separately

| SPGI.2004151 | Lid                           |
|--------------|-------------------------------|
| SPGI.2003080 | 1/6 GN Round Basket           |
| SPGI.2003045 | 1/6 GN Basket - right handle  |
| SPGI.2003047 | 1/6 GN Basket - left handle   |
| SPGI.2003046 | 1/3 GN Basket - left to right |
| SPGI.2003075 | 2/3 GN Basket                 |
| SPGI.2003077 | 1/3 GN Basket - front to back |



www.stoddart.com.au www.stoddart.co.nz

