

FG9821PT

Fryer - Gas, Double Pan, 21 + 21 Litre / Base







Product Information:

- · Class leading, European style, professional quality and reliability since 1963
- 900 series, electric 2 x 21 litre, double pan fryer (136.8 MJ/h)
- Open pan design with external burners
- Electronic ignition, high efficiency, stainless steel burners complete with flame failure device, pilot burner and Hi-limit temperature protection with manual reset
- Temperature regulation via thermostat ($100^{\circ}\text{C} 195^{\circ}\text{C}$)
- Thermostat bulbs protected against accidental impact
- Cold zone on the bottom of the tank to collect residues and prevent tainting of oil
- 2x 310x444mm single tanks with oil drainage via ball valve into integrated oil capture drawer
- · Indicator lights to monitor the correct operation of the appliance
- Robust 304 grade stainless steel construction with rounded corners for improved cleaning
- Pressed top work surface with raised edges to protect from overflow
- Enclosed base with front access doors
- Height adjustable stainless steel feet for a 900mm working height
- Supplied with removable mesh basket support, 4x 146x400x120mm baskets and lids
- 24-month warranty

General Drawing:





Due to continuous product research and development, the information contained herein is subject to change without notice. Revision: 01 - 15/11/2021 - A

www.stoddart.com.au www.stoddart.co.nz







Specifications:

Model	FG9821PT	
W x D x H (mm)	800 x 920 x 1054	
Weight	145kg	
Oil Capacity	2 x 21L	
Packed Dimensions (mm)	845 x 1025 x 1200	
Packed Weight (mm)	157kg	
Electrical Connection	1Ø + N + E	
	240VAC / 50Hz / 0.2kW	

	Natural	Universal LPG
Gas Connection	1/2" BSP	1/2" BSP
Minimum Normal Test Gas Pressure	1.3 kPa	2.75 kPa
Maximum Normal Test Gas Pressure	3.5 kPa	3.5 kPa
Nominal Test Point Pressure	1.0 kPa	2.65 kPa
Total Nominal Gas Consumption	136 8 M J/h	136.8 M J/h

10A plug & lead fitted

Note: It is the responsibility of the installing gas plumber to ensure correct supply and connection sustaining appropriate pressure, when all installed gas appliances are operating at maximum.

Legend:

Gas Connection В Electrical Connection