### **TROUGHS**

# Chilled Drink Trough - with Chilled Water to Fascia Mounted Bubbler Taps & Accessible End Bubbler

### Model: SPPL.DT.DC.x.P.2000

SPPL = Stoddart Plumbing Product

DT = Drinking Trough
D = Disabled Access
C = Chilled drink taps
x = L = Left Hand Waste
= R = Right Hand Waste
P = Fully plumbed
2000 = 2000mm long unit

eg.: for specification and ordering quote

Code: SPPL.DT.DC.L.P.2000

### **Specifications:**

Construction: 1.5mm thick, 304 grade stainless steel

construction, no.4 satin finish

Water Connection: 1/2" BSP water connection required with

capacity to supply

Waste Connection: 50mm, PVC waste supplied, trap is not included

Taps: Taps come standard with push button activation

Unit Fixing: Optional floor mounted frame available upon

request

Chiller: 240VAC, 50Hz, 370W, (3A Max Draw). ARI1010-


94 Standard Performance is; 27° In to 10° Out with 32° Ambient. Factory preset thermostat @

10°.


Model No.	L x D x H (mm)	No. of Bubblers	Cooling Capacity
DT.DC.L.P.2000	2000 x 600 x 702	4 (3 abled & 1 access)	Output flow of 2 cups/minute below 15°C can be obtained from 25°C input supply water
DT.DC.R.P.2000	2000 x 600 x 702	4 (3 abled & 1 access)	




- Designed for schools and sports clubs
- Concealed plumbing and fixings for vandal resistance
- Powerful Australian water chiller provides continuous supply of cool, refreshing water to the drink taps
- Chiller has a 2M lead with 10A, 3 pin plug
- · Standard taps have push buttons
- Bubblers are fitted with safe mouth guards to protect teeth from damage
- · Environmentally conscious on/off push action saves water
- Water height control valve allows water trajectory to be adjusted
- Disabled access compliant end outlet
- Optional bottle filler requires 300mm splashback



riali view



Front View



End View

## Sold Separately

Tapware Options:



CMPL.0931







