

Product Information

- High efficiency cooktops with heavy duty electronic components and thick, high-impact Schott Ceran glass-ceramic top, engineered for use in commercial kitchens
- Easy control via the Helios Standard interface
- Temperature range from 29°C 218°C
- Automatic pan detection for instant energy transmission to the pan & almost no energy consumption when the pan is not present
- Microprocessor monitors vital components to check for overheating and power supply issues
- Automatic shut-off feature prohibits overheating
- Drop-in units feature Stainless steel edging, aluminium housing and
- Integral grease filter and air baffle to ensure cleaner and cooler air intake for optimum reliability
- 24-month parts and 12-months labour warranty





Specifications

Model HRD.9500.SH25.4 HRD.9500.SH35.4 W x D x H (mm) 343 x 343 x 93 343 x 343 x 93 7kg

Weight 7kg

Total Connected Load 2.4kW

Electrical Connection 1Ø + N + E 240VAC / 50Hz 1Ø + N + E 240VAC / 50Hz

> 10A plug & lead (1.8m) 15A plug & lead (1.8m)

Cut Out Size (mm) 334w x 334d 334w x 334d

476 x 527 x 229 / 11kg 476 x 527 x 229 / 11kg Shipping

Legend

Electrical Connection





