

Product Information

- High efficiency cooktops with heavy duty electronic components and thick, high-impact Schott Ceran glass-ceramic top, engineered for use in commercial kitchens
 - Easy control via the Helios Standard interface
 - Temperature range from 29°C - 218°C
 - Automatic pan detection for instant energy transmission to the pan & almost no energy consumption when the pan is not present
 - Microprocessor monitors vital components to check for overheating and power supply issues
 - Automatic shut-off feature prohibits overheating
 - Drop-in units feature Stainless steel edging, aluminium housing and control box
 - Integral grease filter and air baffle to ensure cleaner and cooler air intake for optimum reliability
 - 1.2mm thick 304 stainless steel bench top
 - 3mm zinc anneal steel reinforced backing to work top
 - 38mm diameter round stainless steel tube legs, 1.2mm thick
 - Adjustable stainless steel disk feet fitted as standard
 - 1.2mm thick stainless steel under-shelf with top hat stiffening
- 24-month parts and 12-months labour warranty



Specifications

Model	HRD.9500.FB25.4.1200	HRD.9500.FB35.4.1200
W x D x H (mm)	1200 x 805 x 1050	1200 x 805 x 1050
Weight	94kg	94kg
Total Connected Load	4.8kW x3	7kW x3
Electrical Connection	1Ø + N + E 240VAC / 50Hz 20A plug & lead (1.8m) x3	1Ø + N + E 415VAC / 50Hz Lead only (1.8m) 32A plug required x3
Shipping	1300 x 830 x 1200 / 99kg	1300 x 830 x 1200 / 99kg

