TROUGHS

Chilled Drink Trough - with Chilled Water to Fascia Mounted Bubbler Taps & Accessible End Bubbler

.

Model: SPPL.DT.DC.x.P.2000

- SPPL = Stoddart Plumbing Product
- DT = Drinking Trough D = Disabled Access
- C = Chilled drink taps
- x = L = Left Hand Waste
- = R = Right Hand Waste
- P = Fully plumbed
- 2000 = 2000mm long unit
- eg.: for specification and ordering quote Code: SPPL.DT.DC.L.P.2000

Features and Benefits:

- Designed for schools and sports clubs
- Concealed plumbing and fixings for vandal resistance
- Powerful Australian water chiller provides continuous supply of cool, refreshing water to the drink taps
- Chiller has a 2M lead with 10A, 3 pin plug
- Standard taps have push buttons
- Bubblers are fitted with safe mouth guards to protect teeth from damage
- Environmentally conscious on/off push action saves water
 - Water height control valve allows water trajectory to be adjusted
- Disabled access compliant end outlet
- Optional bottle filler requires 300mm splashback





Plan View





Sold Separately

Tapware Options:







Specifications:

Construction:	304 grade stainless steel construction, no.4 satin finish	
Water Connection:	1/2" BSP water connection required with capacity to supply	
Waste Connection:	50mm, PVC waste supplied, trap is not included	
Taps:	Taps come standard with push button activation	
Unit Fixing:	Optional wall mounted frame available upon request	
Chiller:	240VAC, 50Hz, 370W, (3A Max Draw). ARI1010- 94 Standard Performance is; 27° In to 10° Out with 32° Ambient. Factory preset thermostat @ 10°.	

Model No.	L x D x H (mm)	No. of Bubblers	Cooling Capacity
DT.DC.L.P.2000	2000 x 600 x 702	4 (3 abled & 1 access)	Output flow of 2 cups/minute below 15°C can be obtained from 25°C input supply water
DT.DC.R.P.2000	2000 x 600 x 702	4 (3 abled & 1 access)	



Due to continuous product research and development, the information contained herein is subject to change without notice. Revision: A - May 29, 2025 10:38 AM

www.stoddart.com.au www.stoddart.co.nz