

Features

- Commercial grade quality and fully backed by our industrial warranty
- Modular one piece of construction with all serviceable components above the basin
- Double infrared sensor with automatic setting feature and microprocessor
- Bi-stable magnetic solenoid valve (for increased energy savings)
- Water supply connection with flexible high-pressure hose and strainer
- Aqua click feature enables temporary - off (for cleaning purposes) or continuous water flow (for filling the basin)
- Check valves and built-in strainers
- Single temperature
- 6V lithium CR-P2 commercial battery included
- 12, 24 or 72-hour hygienic rinse activatable



Technical Information

• WaterMark	AS/NZS 3718 Lic. WMKA20371
• WELS	6 Star Rating (4.5L/min)
• Nominal Flow Rate (LPM)	4.3
• Operating Pressure (kPa)	30Pa - 500kPa
• Maximum Water Temperature (°C)	80
• Aerator	Economy aerator, cascade (self-cleaning)
• Inlet connection	Flexible hose at 350mm long
• Strainer	0.5mm mesh size
• Sensor Sensitivity	Automatic self-adapting sensor technology
• Sensor Range Nominal (mm)	102 - 127
• Hygiene Rinse Time	2 Minutes pre-set (adjustable 0.5 - 20 minutes)
• Temporary Off	2 Minutes (fixed)
• Time Out Setting	2 Minutes - Maximum time tap will run upon continuous detection
• Power Supply	6V Lithium CR-P2 Commercial Battery
• Engineering Standards	Noise class I, DIN EN 200; P-IX 9576 / IA

