

### Product Information

- High efficiency cooktops with heavy duty electronic components and thick, high-impact Schott Ceran glass-ceramic top, engineered for use in commercial kitchens
  - Easy control via the Helios Standard interface
  - Temperature range from 29°C - 218°C
  - Automatic pan detection for instant energy transmission to the pan & almost no energy consumption when the pan is not present
  - Microprocessor monitors vital components to check for overheating and power supply issues
  - Automatic shut-off feature prohibits overheating
  - Drop-in units feature Stainless steel edging, aluminium housing and control box
  - Integral grease filter and air baffle to ensure cleaner and cooler air intake for optimum reliability
  - 1.2mm thick 304 stainless steel bench top
  - 3mm zinc anneal steel reinforced backing to work top
  - 38mm diameter round stainless steel tube legs, 1.2mm thick
  - Adjustable stainless steel disk feet fitted as standard
  - 1.2mm thick stainless steel under-shelf with top hat stiffening
- 24-month parts and 12-months labour warranty



### Specifications

<b>Model</b>	HRD.9500.FB25.4.0450	HRD.9500.FB35.4.0450
<b>W x D x H (mm)</b>	450 x 805 x 1050	450 x 805 x 1050
<b>Weight</b>	39kg	39kg
<b>Total Connected Load</b>	4.8kW	7kW
<b>Electrical Connection</b>	1Ø + N + E 240VAC / 50Hz 20A plug & lead (1.8m)	1Ø + N + E 240VAC / 50Hz Lead only (1.8m) 32A plug required
<b>Shipping</b>	500 x 830 x 1200 / 44kg	584 x 813 x 279 / 44kg

