

Product Information

- High performance XL hood-type dishwasher with pre-fitted, easy to install energy savings device (ESD)
- Electronic Pro Interface** - advanced functionality
- PRS System:** break tank, 316 atmospheric boiler, rinse booster pump
- HD System:** for maximum uninterrupted performance
- ES System:** energy savings device (ESD)
- Double skin insulated hood
- Increased capacity with 600x500mm baskets (500 x 500mm compatible)
- XL Filters robust with additional upper tank scrap filter
- Larger HP vertical self-draining wash pump
- Larger HI FLOW stainless steel wash and rinse arms
- Larger elements in wash tank and boiler
- Four wash cycles 90/120/180 seconds, and 9 minute deep clean
- Green standby function that reduces energy consumption when idle
- Low water consumption of 2.5 litres per cycle, minimising water, energy and detergent use
- Pressed wash tank with rounded corners, for increased hygiene
- Manual lift with fully enclosed rear, 3 spring support
- Automatic drain pump with self-cleaning function
- Built in thermostop, ensures correct rinse temperatures
- Built in detergent and rinse-aid injection
- 24-months parts and labour warranty

Included Accessories

- 1 x glass rack 500 x 600mm
- 2 x plate rack 500 x 600mm
- 2 x cutlery basket
- 1 x water inlet hose (length 1.5m)
- 1 x drain hose (length 2m)
- Fitted with 150mm adjustable legs

Optional Accessories

- Twin hood system
- Remote interface
- Inlet and outlet benches
- Additional baskets

Specifications

Model	AH60.42EPI.ES
W x D x H (mm)	681 x 793 x 2294
Note: Dimensions do not include handle. Hood open	
Weight	179kg
Packed Dimensions (mm)	770 x 930 x 1870
Packed Weight	198kg
Total Connected Load	14.8kW / 415VAC, 25A circuit L1 = 21A / L2 = 21A / L3 = 21A
Convertible to: (Low Power Option)	10.3kW / 415VAC, 15A circuit L1 = 15A / L2 = 15A / L3 = 15A
Note: Unit can be converted to low power option on site by a qualified electrician. This may affect the output of the unit.	
Electrical Connection	3Ø+N+E 415VAC / 50Hz (Lead fitted, on-site connection)
Water Quantity Per Cycle	2.5 Litres
Water Connection	1.5m Hose / 3/4" BSP
Water Inlet Pressure	100 - 500KPA
Tempered water supply	10°C - 25°C
Waste Connection	2m Hose / ø20.5mm

Legend

A Electrical Connection **D** Detergent Line
B Water Connection **E** Rinse-Aid Line
C Drain Connection

