


Wash Basin Knee Operated - Type 1

Model: SPPL.WB.KO1.xxx.yy


SPPL = Stoddart Plumbing Product
 WB = Wash Basin
 KO1 = Knee operated, without lower plumbing shroud
 xxx = 300 = 300mm splashback
 yy = TV = Tempering valve
 = TMVE = Thermostatic mixing valve
 eg.: for specification and ordering quote
 Code: SPPL.WB.KO1.300.TV

Features and Benefits:

- Hygienic hands free use with knee operated front panel
- Pressing the front panel activates the timed flow of water from the spout
- Replacement valves for the timed flow valve are available as a spare part
- Lead free compliant
- This basin when fitted with a tempering valve, complies with AS4674 for fit out of food premises
- Water is supplied through an aerated, high rise spout for easy access and minimal splash
- Spout is WELS rated spout for controlled flow to 7.5 litres per minute
- Easy-mount single piece stainless steel wall bracket has multiple fixing holes for quick installation by plumber
- Optional 300mm splashback is available, eliminating the need for a tiled splashback



Plan View



Specifications:


Construction: 304 grade stainless steel construction, wand operated valve and spout are pre-plumbed.

Water Connection: 15mm, 1/2" BSP. For addition of optional TV or TMVE, hot and cold supplies are required. Component claimed temperature control;
 • Thermostatic Mixing Valve = +/- 2 deg C
 • Tempering Valve = +/- 3 deg C
 Additional water strainer/filter to protect valves from water-borne dirt and scale is fitted as standard.


Waste Connection: 40mm PVC waste supplied (Trap by others)

Unit Fixing: Unit is supplied with wall mounting bracket with 10mm fixing holes. Optional TV or TMVE is supplied as a loose kit part for plumber to install in compliance with regulations. Optional splashback supplied loose, fix to wall with double sided tape and silicon around edges to seal.

Fixing Height: The unit should be mounted at 800 – 830mm above finished floor level for disabled user access.



Front View



End View

Model No.	L x D x H (mm)
SPPL.WB.KO1.xxx.yy	500 x 420 x 160 (326 with spout)



Due to continuous product research and development, the information contained herein is subject to change without notice.

Revision: G - 29/20/2026 - 03

www.stoddart.com.au
 www.stoddart.co.nz