

### Product Information

- High performance XL hood-type dishwasher
- **Electronic Pro Interface** - advanced functionality
- **PRS System:** break tank, 316 atmospheric boiler, rinse booster pump
- **HD System:** for maximum uninterrupted performance
- Double skin insulated hood
- Increased capacity with 600x500mm baskets (500 x 500mm compatible)
- XL Filters robust with additional upper tank scrap filter
- Larger HP vertical self-draining wash pump
- Larger HI FLOW stainless steel wash and rinse arms
- Larger elements in wash tank and boiler
- Four wash cycles 90/120/180 seconds, and 9 minute deep clean
- Green standby function that reduces energy consumption when idle
- Low water consumption of 2.5 litres per cycle, minimising water, energy and detergent use
- Pressed wash tank with rounded corners, for increased hygiene
- Manual lift with fully enclosed rear, 3 spring support
- Automatic drain pump with self-cleaning function
- Built in thermostop, ensures correct rinse temperatures
- Built in detergent and rinse-aid injection
- **24-months parts and labour warranty**

### Included Accessories

- 1 x glass rack 500 x 600mm
- 2 x plate rack 500 x 600mm
- 2 x cutlery basket
- 1 x water inlet hose (length 1.5m)
- 1 x drain hose (length 2m)
- Fitted with 150mm adjustable legs

### Optional Accessories

- Twin hood system
- Remote interface
- Inlet and outlet benches
- Additional baskets



### Specifications

|   |   |
|---|---|
| <b>Model</b>  | AH60.42EPI.PRS  |
| <b>W x D x H (mm)</b>   | 681 x 793 x 2016*   |
| Note: Dimensions do not include handle. Hood open   |   |
| <b>Weight</b>   | 141kg   |
| <b>Packed Dimensions (mm)</b>   | 770 x 930 x 1720  |
| <b>Packed Weight</b>  | 160kg   |
| <b>Total Connected Load</b>   | 14.8kW / 415VAC, 25A circuit<br>L1 = 21A / L 2 = 21A / L3 = 21A |
| <b>- Convertible to:</b>  | 10.3kW / 415VAC, 15A circuit                                    |
| (Low Power Option)  | L1 = 15A / L 2 = 15A / L3 = 15A                                 |
| Note: Unit can be converted to low power option on site by a qualified electrician. This may affect the output of the unit. |   |
| <b>Electrical Connection</b>  | 3Ø+N+E 415VAC / 50Hz<br>(Lead fitted, on-site connection)       |
| <b>Water Quantity Per Cycle</b>   | 2.5 Litres  |
| <b>Water Connection</b>   | 1.5m Hose / 3/4" BSP  |
| <b>Water Inlet Pressure</b>   | 100 - 500KPA  |
| <b>Tempered water supply</b>  | 10°C - 60°C   |
| <b>Waste Connection</b>   | 2m Hose / ø20.5mm   |

### Legend

- A Electrical Connection    D Detergent Line  
 B Water Connection        E Rinse-Aid Line  
 C Drain Connection

