

Product Information

- High performance XL hood-type dishwasher with pre-fitted, easy to install energy savings device (ESD)
- **Electronic Pro Interface** - advanced functionality
- **PRS System:** break tank, 316 atmospheric boiler, rinse booster pump
- **HD System:** for maximum uninterrupted performance
- Double skin insulated hood
- Increased capacity with 600x500mm baskets (500 x 500mm compatible)
- XL Filters robust with additional upper tank scrap filter
- Larger HP vertical self-draining wash pump
- Larger HI FLOW stainless steel wash and rinse arms
- Larger elements in wash tank and boiler
- Four wash cycles 90/120/180 seconds, and 9 minute deep clean
- Green standby function that reduces energy consumption when idle
- 2.5L per cycle reduces water, energy and detergent use.
- Pressed wash tank with rounded corners, for increased hygiene
- Manual lift with fully enclosed rear, 3 spring support
- Automatic drain pump with self-cleaning function
- Built in thermostat, ensures correct rinse temperatures
- Built in detergent and rinse-aid injection
- This Aristarco dishwasher has been tested & complies with the requirement of current building code of Australia NCC2025-Part1, subject to conditions and limitations listed in certification document. Testing conducted independently by Australian National Testing Laboratories PTY LTD (ANTL) – Test report 5608.13.
- **24-months parts and labour warranty**

Note: The enclosure must have a minimum of 180 l/s of the air replaced by either general exhaust ventilation, supply ventilation, natural ventilation, or a combination of these. Where other heat or steam-generating appliances share the enclosure or room, the airflow must be increased to accommodate those appliances.

Note: The room requirement for multiple units may not be the "l/s air" sum of the tested individual units.

Included Accessories

- 1 x glass rack 500 x 600mm
- 2 x plate rack 500 x 600mm
- 2 x cutlery basket
- 1 x water inlet hose (length 1.5m)
- 1 x drain hose (length 2m)
- Fitted with 150mm adjustable legs

Optional Accessories

- Twin hood system
- Remote interface
- Inlet and outlet benches
- Additional baskets

Specifications

Model AH60.42EPI.ES
W x D x H (mm) 681 x 793 x 2294

Note: Dimensions do not include handle. Hood open

Weight 179kg

Packed Dimensions (mm) 770 x 930 x 1870

Packed Weight 198kg

Total Connected Load 14.8kW / 415VAC, 25A circuit
 L1 = 21A / L 2 = 21A / L3 = 21A

- Convertible to: 10.3kW / 415VAC, 15A circuit
 (Low Power Option) L1 = 15A / L 2 = 15A / L3 = 15A

Note: Unit can be converted to low power option on site by a qualified electrician. This may affect the output of the unit.

Electrical Connection 3Ø+N+E 415VAC / 50Hz
 (Lead fitted, on-site connection)

Water Quantity Per Cycle 2.5 Litres

Water Connection 1.5m Hose / 3/4" BSP

Water Inlet Pressure 100 - 500KPA

Tempered water supply 10°C - 25°C

Discharge Water Temp. Max 82°C

Waste Connection 2m Hose / ø20.5mm

Legend

- | | |
|--------------------------------|-------------------------|
| A Electrical Connection | D Detergent Line |
| B Water Connection | E Rinse-Aid Line |
| C Drain Connection | |

