

#### Product Information

- High performance XL hood-type dishwasher
- **Electronic Pro Interface** - advanced functionality
- **PRS System**: break tank, 316 atmospheric boiler, rinse booster pump
- **HD System**: for maximum uninterrupted performance
- Double skin insulated hood
- Increased capacity with 600x500mm baskets (500 x 500mm compatible)
- XL Filters robust with additional upper tank scrap filter
- Larger HP vertical self-draining wash pump
- Larger HI FLOW stainless steel wash and rinse arms
- Larger elements in wash tank and boiler
- Four wash cycles 90/120/180 seconds, and 9 minute deep clean
- Green standby function that reduces energy consumption when idle
- Low water consumption of 2.5 litres per cycle, minimising water, energy and detergent use
- Pressed wash tank with rounded corners, for increased hygiene
- Manual lift with fully enclosed rear, 3 spring support
- Automatic drain pump with self-cleaning function
- Built in thermostat, ensures correct rinse temperatures
- Built in detergent and rinse-aid injection
- **24-months parts and labour warranty**

#### Included Accessories

- 1 x glass rack 500 x 600mm
- 2 x plate rack 500 x 600mm
- 2 x cutlery basket
- 1 x water inlet hose (length 1.5m)
- 1 x drain hose (length 2m)
- Fitted with 150mm adjustable legs

#### Optional Accessories

- Twin hood system
- Remote interface
- Inlet and outlet benches
- Additional baskets



#### Specifications

|                                                   |                   |
|---------------------------------------------------|-------------------|
| <b>Model</b>                                      | AH60.42EPI.PRS    |
| <b>W x D x H (mm)</b>                             | 681 x 793 x 2016* |
| Note: Dimensions do not include handle. Hood open |                   |
| <b>Weight</b>                                     | 141kg             |
| <b>Packed Dimensions (mm)</b>                     | 770 x 930 x 1720  |
| <b>Packed Weight</b>                              | 160kg             |

|                                                |                                                                 |
|------------------------------------------------|-----------------------------------------------------------------|
| <b>Total Connected Load</b>                    | 14.8kW / 415VAC, 25A circuit<br>L1 = 21A / L 2 = 21A / L3 = 21A |
| <b>- Convertible to:</b><br>(Low Power Option) | 10.3kW / 415VAC, 15A circuit<br>L1 = 15A / L 2 = 15A / L3 = 15A |

Note: Unit can be converted to low power option on site by a qualified electrician. This may affect the output of the unit.

|                              |                                                           |
|------------------------------|-----------------------------------------------------------|
| <b>Electrical Connection</b> | 3Ø+N+E 415VAC / 50Hz<br>(Lead fitted, on-site connection) |
|------------------------------|-----------------------------------------------------------|

|                                 |                      |
|---------------------------------|----------------------|
| <b>Water Quantity Per Cycle</b> | 2.5 Litres           |
| <b>Water Connection</b>         | 1.5m Hose / 3/4" BSP |
| <b>Water Inlet Pressure</b>     | 100 - 500KPA         |
| <b>Tempered water supply</b>    | 10°C - 60°C          |
| <b>Discharge Water Temp.</b>    | Max 82°C             |
| <b>Waste Connection</b>         | 2m Hose / ø20.5mm    |

#### Legend

|                                |                         |
|--------------------------------|-------------------------|
| <b>A</b> Electrical Connection | <b>D</b> Detergent Line |
| <b>B</b> Water Connection      | <b>E</b> Rinse-Aid Line |
| <b>C</b> Drain Connection      |                         |

