

Want to de-risk while speeding

Danfoss

ENGINEERING TOMORROW

HIGHLIGHTS

Optimize your overview

- Maintain full transparency by simulating the drive at parameter level
- Assess product and system
 performance before
 prototyping
- Software always up-to-date

Design efficiently

- Use only the simulation modules you need
- Balance speed and level of detail as required

Speed up and de-risk

- Speed up product
 development
- De-risk project execution by avoiding potential issues early
- Reduce time and cost of lab testing and on-site commissioning
- Improve safety for personnel



up **product development?**

Get started faster

With MyDrive[®] Virtual, we offer you the same product insights achievable by physically testing a real iC7 drive.

Simulation for iC7 series: MyDrive® Virtual

MyDrive[®] Virtual gives you drive models which you can use in your preferred simulation environment. MyDrive[®] Virtual uses the same source models as the physical drive software, to guarantee high fidelity.

Just imagine a new approach to development, which gets you to market faster. Which gives you the freedom to act on the thought: 'what if?' Imagine testing every corner of your idea with no risk of downtime, and without paying for prototypes.

By eliminating the constraints of the physical environment, you can achieve higher test coverage, and thoroughly test automation to reduce time to market.

Save cost and time

The prototypes used in new product development are very costly and time-consuming to develop, build, and maintain. With MyDrive® Virtual , you can eliminate prototypes and de-risk project execution by identifying and removing sources of failure much earlier in the development phase. You also save on laboratory time, space, and energy consumption.

With MyDrive® Virtual you can optimize the performance down to parameter level and thereby save money thanks to faster on-site commissioning.

1:1 Digital Twin

Use the same firmware control software and application software as the physical drive, for best-in-class simulation results, with no room for error.

Use your preferred environment

The simulation models are available in a standardized format compatible with over 150 major simulation tools, worldwide. So there's no need to invest in a new simulation environment. Just use your existing tool.

What can I use it for?

Use MyDrive® Virtual to

- De-risk project execution throughout the product lifecycle
- Assess overall performance of the whole system before using physical components
- Eliminate cost of developing prototypes and transporting them
- Reduce commissioning time on site
- Freely choose the iC7 simulation model that best meets the demands of your application.

Engineering

- Optimize system performance and energy consumption
- Evaluate diverse configurations
- Reduce the overall testing time and less needs of physical test-setups due to virtual testing
- Enable end-to-end system simulations to increase system performance

Testing

- Increase test coverage with test
 automation
- Remove time spent on building up the physical test setup
- Benchmark different drive sizes and motor types without physical hardware
- Reduce laboratory time for testing
- Reduce need for equipment
- Improve safety by testing critical scenarios in an un-stressful environment and without risk of damaging the equipment

Installation and commissioning

- Reduce commissioning time thanks to less need for physical testing
- Fine tune up-front to optimize application performance
- Run learning and testing activities on virtual applications

Maintenance and service

- Build digital twins of your products to continuously improve and monitor performance and processes
- Save process data for later use in optimization
- Improve the product with no production stop
- De-risk software updates by virtually testing first
- Test different scenarios to optimize them
- Identify sporadic failures with reduced effort
- Share configuration data and results easily

How does it work?

With the modular concept, you can choose the MyDrive® Virtual models which best reflect your requirements. In this way, you can simulate a wide variety of use cases. MyDrive® Virtual is built from the same source models as the physical drive software, to guarantee high accuracy. Each application model behaves identically to the drive, making it ideal for configuration and logic simulations. The iC7 drive-train model includes control firmware, enabling you to simulate actual control algorithms in the drive to evaluate power sizes and machine performance.

Appication software	Control firmware	Converter model	Machine models	Load models	Simulation models
					Application model
					Drive model
	\checkmark	\checkmark	\checkmark		Drive-train model
	Ø				Drive system model

Select the models you need 1. Simulation using AC drive models

2. Simulation using power converter models

	Appication software	Control firmware	Converter model	Machine models	Load models	Simulation models
	\checkmark					Application model
7		S	Ø			Converter model
	\checkmark			\checkmark		Grid-train model
		Ø	Ø		Ø	Grid system model

Your choice of environment

Use the MyDrive® Virtual models in your preferred simulation environment.

iC7 series drive-train model in Matlab Simulink simulation environment



	cumentation F	ile					
Parameters	Simulation	Input	Output				
Filter by nam	e or description						
	P	arameter		Value	Unit	Description	
Propuls	sionApp						
Y 🗄 Valu	e						
~ 🖻 N	11_Grid						
> 📑	M1_2_Grid_Se	ettings					
¥ 🖪	M1_3_Grid_Pr	otection					
	P1_3_1_Inv	alid_Frequ	ency_Response	int32(1)		PropulsionApp.Value.	
	P1_3_2_Mit	ssing_Pha	se_Response	int32(1)		PropulsionApp.Value.	
	P1_3_3_Un	dervoltag	e_Protection	boolean(1)		PropulsionApp.Value.	
	12_Power_Conv						
	13_Filters_Brak	e_Choppe	H				
	Motor						
	15_Application						
	16_Maintenano	e_Service					
> 🖪 N							
	110_Connectivit	ty					
Motor							
Valu							
	lotorSelection			int32(2)		Motor.Value.MotorSel	
	10_efa280V400						
	11_eta315V400 12_editron_EMF						
DriveSi		MI57511	1002900				
 E Valu 							
	e riveSizeSetup			int32(1)		DriveSize Value Drive	
D0 IC7 60 FX11 3N05 588A				int32(0)		DriveSize.Value.D0 iC.	

iC7 series model in FMPy simulation environment

File Tools Help								
	Co-Simulatio	n Y			Y + =			
ter una tane 0	Start	0 0 0 0 0	Plot	Description (red), more DMA HD (red), more DMA HD (red), more DMA DMB (red), more DMA (red), more	v v ≡	Event I Variabi Genera Genera Descrip Simulatio Soliver Step Si Relative O Qu	version 2. ypa Cr. Name	Image: Second
	k	0		Sets the mode for the preset reference. Sets the number of the preset reference to be u Setset the Input terminal for pelecting between Res Facility Input Reports Time Time Time Time			put phy default star g FRII calls ibug Logging	start volues



iC7 series model in Dymola simulation environment



Danfoss

Features and benefits

Feature	Benefit
De-risk project execution in an early phase	Greater reliability in business model
Easily simulate different power sizes together with different motor types, filters, for early integration of individual components	Enables you to invest in the optimal solution both cost- and perfor- mance-wise.
Assess efficiency of alternative configurations in the design phase	Reduce energy consumption in the application
Minimize the extent of building test set-ups and performing physical testing by maximizing virtual testing	Reduce overall testing time and cost
Optimize parameters during the design phase	Reduce commisioning time
Capacity to run end-to-end system simulations	Improve system performance and de-risk project execution
 High level of automation during testing Test critical scenarios in a low-stress environment Eliminate risk of equipment damage 	Improve safety
 Capability to build a digital twin of your products to continuously monitor and improve performance Facilitates virtual system validation of software updates 	Efficiently maintain and improve the application over its lifetime

Supports over 150 tools globally

FMI-compliant for maximum compatibility

The iC7 models are compatible with over 150 simulation environments due to the Functional Mock-Up Interface Standard. It is used by automotive and non-automotive organizations throughout Europe, Asia and North America.

- Many simulation tools are supported:
- MATLAB & Simulink
- Ansys Twin Builder
- SIMIT
- Dymola
- DÍgSILENT
- FMPy

FMI is an open standard for exchanging dynamic simulation models between different tools in a standardized format. You can select the tool best suited for each type of analysis, while keeping the same model.

MyDrive® Virtual complies with FMI.

Functional Mock-Up Interface



Read more about the **fmi standard here** 🗹

AM418529686475en-000202 | © Copyright Danfoss Drives | 2023.10

Any information, including, but not limited to information on selection of product, its application or use, product design, weight, dimensions, capacity or any other technical data in product manuals, catalogues descriptions, advertisements, etc. and whether made available in writing, orally, electronically, online or via download, shall be considered informative, and is only binding if and to the extent, explicit reference is made in a quotation or order confirmation. Danfoss cannot accept any responsibility for possible errors in catalogues, brochures, videos and other material. Danfoss reserves the right to alter its products without notice. This also applies to products ordered but not delivered provided that such alterations can be made without changes to form, fit or function of the product. All trademarks of Danfoss AFS. All rights reserved.