## **Product Specification**

## 120 GB C Series SATA III 2.5" SSD



The Integral C Series SSD is an excellent choice for increasing storage and boosting performance for your desktop or laptop PC. With a fantastic combination of fast data read/write and reliability, along with low power operation, the Integral C Series offers excellent great value.

- 2.5-inch form factor with SATA III 6Gbps interface (backward compatible with SATA 3Gbps and SATA 1.5Gbps)
- Performance: Faster boot than HDD, Faster access to applications, enhanced productivity and increased efficiency
- Fully compatible with devices and OS that support the SATA standard
- Non-volatile Flash Memory for outstanding data retention
- Shock resistance no moving parts enable the product to be used in tougher conditions
- Silent operation Noiseless
- Ultra-efficient Block Management and Wear Levelling
- Supports S.M.A.R.T. Self-Monitoring, Analysis and Reporting Technology CE, FCC, UKCA, and RoHS compliant
- 3 year warranty or TBW whichever is earlier applies

| SKU | INSSD120GS625C1 |  |
|-----|-----------------|--|
| EAN | 5055288443754   |  |

|           | Width (mm) | Depth (mm) | Height (mm) | Weight (g) |
|-----------|------------|------------|-------------|------------|
| Product   | 69.8       | 100.2      | 7           | 45         |
| Packaging | 107        | 13         | 133         | 64         |

| Capacity (GB)                            | 120     |
|--|---------|
| Component for                            | PC      |
| Form factor                              | 2.5"    |
| ECC (Y/N)                                | Υ       |
| Mean time between failures (MTBF) (hour) | 1500000 |
| TBW rating                               | 60      |
| Flash type                               | TLC     |
| NVMe (Y/N)                               | N       |
| S.M.A.R.T. support (Y/N)                 | Υ       |
| TRIM support (Y/N)                       | Υ       |
| Read speed (MB per second)               | 515     |
| Write speed (MB per second)              | 400     |
| Operating voltage (Volt)                 | 5       |
| Power consumption (read) (Watt)          | 1.45    |
| Power consumption (write) (Watt)         | 1.5     |
| Hardware encryption (Y/N)                | N       |

| Interface                                     | Serial ATA III |
|---|----------------|
| Operating temperature (T-T) (degrees Celcius) | 0 - 70         |
| Storage temperature (T-T) (degrees Celcius)   | -40 - 85       |
| Operating relative humidity (H-H) (percent)   | 0 - 90         |
| Operating shock (gravity)                     | 1500           |
| Sustainability certificates                   | RoHS           |
| Certification                                 | CE, FCC, UKCA  |