Product Specification

1920 GB UltimaPro X SATA III 2.5 SSD TCG OPAL 2.0 Version 2



The UltimaPro X is Integral s extreme performance SSD that can meet your most demanding gaming, graphic design, and video workflow needs. Ideal for gamers and power-users who demand extreme performance, the Integral UltimaPro X range of Solid State Drives are specifically engineered to compliment high-spec machines and provide the best gaming and multimedia application performance. The Integral UltimaPro X range offers extreme performance at great value

- 2.5 inch form factor with SATA III 6Gbps interface (backwards compatible with SATA 3Gbps and SATA 1.5Gbps)
- Non-volatile Flash Memory for outstanding data retention
- Ultra-efficient Block Management and Wear Levelling
- Supports S.M.A.R.T. Self-Monitoring, Analysis and Reporting Technology
- 3 year warranty or TBW whichever is earlier applies

	Width (mm)	Depth (mm)	Height (mm)	Weight (g)
EAN	5055288442863			
SKU	INSSD1920GS625UPX2			

	Width (mm)	Depth (mm)	Height (mm)	Weight (g)
Product	69.8	100	7	50
Packaging	107	13	133	64

Capacity (GB)		
Form factor	2.5"	
ECC (Y/N)		Y
Mean time between failures (MTBF) (hour)		2000000
TBW rating		3675
Flash type	TLC	
NVMe (Y/N)		Ν
S.M.A.R.T. support (Y/N)		Y
TRIM support (Y/N)		
Data transfer rate (GB per second)		6
Read speed (MB per second)		560
Write speed (MB per second)		530
Random read (4KB) (Input/Output Operations Per Second)		82000
Random write (4KB) (Input/Output Operations Per Second)		83000
Operating voltage (Volt)		5
Power consumption (read) (Watt)		
Power consumption (write) (Watt)	2	
Hardware encryption (Y/N)		Ν
Interface	Serial ATA III	
Operating temperature (T-T) (degrees Celcius)	0 - 70	

Interface	Serial ATA III
Operating temperature (T-T) (degrees Celcius)	0 - 70
Storage temperature (T-T) (degrees Celcius)	-40 - 85
Operating relative humidity (H-H) (percent)	0 - 90
Non-operating shock (gravity)	1500
Certification	CE, FCC