Product Specification

1 TB (1000 2B4G) CPTR Y0MMM. 0 PG8I ENY I SSV (M0M0 Y RV I D4

FIPS 140-2 Level 3 Validated - Certificate No. 3970. Integral Crypto M.2 2280 PCIe NVMe SSD is the Full Disk Encryption solution for Windows laptops and Ultrabooks. If an ultrabook or laptop with an Integral Crypto M.2 2280 PCIe NVMe SSD installed is lost or stolen, sensitive data is secure and cannot be accessed without the highstrength password. When the system is shut down, 256-bit full disk encryption is instigated.

- Mandatory encryption
- Secure Entry - Encrypted data cannot be accessed without the correct high-strength 8-16 character alphanumeric password. Before use a high-strength password must be set
- Tamper-proof Design - The electronics are sealed in tamperfree epoxy resin
- FIPS 140-2 Level 3 Validated - Certificate No. 3970
- High-speed Read/Write - up to 3400MB/s* and 3100MB/s*
- Quick Boot - Using a solid state disk in place of a traditional hard drive can cut your desktop computer or laptop s boot time in half
- Shockproof - no moving parts, so a greater resistance to shock and vibration than HDD
- Silent operation and low heat for a comfortable user experience
- Low power usage - laptop battery will last far longer with SSD than HDD
- Endpoint security software compatible - The Integral Crypto SSD operates comfortably with endpoint security solutions by using the configurable hardware unique ID feature, which is part of the program
- BIOS Independent - Crypto SSD security system runs independently of your system BIOS, unlike other hardware encrypted SSDs
- Seamless encryption - unnoticeable to the user
- Admin and User passwords are configurable
- 3 year warranty

SLK	INSSD1TM280NC140
I UE	5055288445147

	A idtW(h h 4	VeptW(h h 4	meiHWt (h h 4	A eiHWt (H4
Product	22	3.9	80	10
PacgaHinH	125	16	195	70

Gapacitk (2B4	1000
Goh ponent for	PC/Notebook
yorh factor	M.2
I GG (CFE4	Y
Yean tih e /etb een faiwurel (YTBy4 (Wour4	1800000
yval Wtkpe	TLC
ENYe (CFE4	Y
SOY OUO) CTOI upport (CFE4	Y
T) 8Y I upport (CFE4	Y
Vata tranl fer rate (2B per l econd4	6
) ead l peed (YB per l econd4	3400
A rite l peed (YB per l econd4	3100
) andoh read (sLB4 (8nputFRutput Rperationl Per Second4	700000
) andoh b rite (sLB4 (8nputFRutput Rperationl Per Second4	690000
Sequentiawread l peed (UTTR4 (YB per l econd4	3400
Sequentiawb rite l peed (UTTR4 (YB per l econd4	3100