

Product Specification

960 GB C Series SATA III 2.5" SSD



The Integral C Series SSD is an excellent choice for increasing storage and boosting performance for your desktop or laptop PC. With a fantastic combination of fast data read/write and reliability, along with low power operation, the Integral C Series offers excellent great value.

- 2.5-inch form factor with SATA III 6Gbps interface (backward compatible with SATA 3Gbps and SATA 1.5Gbps)
- Performance: Faster boot than HDD, Faster access to applications, enhanced productivity and increased efficiency
- Fully compatible with devices and OS that support the SATA standard
- Non-volatile Flash Memory for outstanding data retention
- Shock resistance - no moving parts enable the product to be used in tougher conditions
- Silent operation - Noiseless
- Ultra-efficient Block Management and Wear Levelling
- Supports S.M.A.R.T. - Self-Monitoring, Analysis and Reporting Technology CE, FCC, UKCA, and RoHS compliant
- 3 year warranty or TBW - whichever is earlier applies

| | |
|------------|-----------------|
| SKU | INSSD960GS625C1 |
| EAN | 5055288443785 |

| | Width (mm) | Depth (mm) | Height (mm) | Weight (g) |
|------------------|-------------------|-------------------|--------------------|-------------------|
| Product | 69.8 | 100.2 | 7 | 45 |
| Packaging | 107 | 13 | 133 | 64 |

| | |
|---|---------|
| Capacity (GB) | 960 |
| Component for | PC |
| Form factor | 2.5" |
| ECC (Y/N) | Y |
| Mean time between failures (MTBF) (hour) | 1500000 |
| TBW rating | 480 |
| Flash type | TLC |
| NVMe (Y/N) | N |
| S.M.A.R.T. support (Y/N) | Y |
| TRIM support (Y/N) | Y |
| Read speed (MB per second) | 530 |
| Write speed (MB per second) | 500 |
| Operating voltage (Volt) | 5 |
| Power consumption (read) (Watt) | 1.6 |
| Power consumption (write) (Watt) | 1.49 |
| Hardware encryption (Y/N) | N |

| | |
|--|----------------|
| Interface | Serial ATA III |
| Operating temperature (T-T) (degrees Celcius) | 0 - 70 |
| Storage temperature (T-T) (degrees Celcius) | -40 - 85 |
| Operating relative humidity (H-H) (percent) | 0 - 90 |
| Operating shock (gravity) | 1500 |
| Sustainability certificates | RoHS |
| Certification | CE, FCC, UKCA |