Product Specification

256GB M.2 2230 NVMe Gen3 x 4PCIe SSD



The Integral Memory M.2 2230 NVMe Gen3 x4 PCIe SSD's compact 2230 form factor is designed to upgrade even the most space limited devices including the Valve Steam Deck, ASUS ROG Ally, Microsoft Surface Pro and other ultra-thin tablets and laptops

- Compact form factor compatible with PCs, NUCs, Microsoft Surface Pro Series, Ultra-thin laptops and tablets, and portable gaming devices
- Guaranteed to work with and fit the Valve Steam Deck and ASUS ROG Ally handheld gaming consoles
- M.2 2230 NVMe 1.3 PCIe Gen3 x4 SSD (PCI Express Gen3: Single port X4 lanes)
- Formidable 3400MB/s read and 3000MB/s write speeds for outstanding processing capabilities
- Size: 2230 (22x30mm)
- Easy to install Single-Sided Chips
- Supports SMART and TRIM commands as well as HMB and AES 256.
- Sophisticated error detection and correction (LDPC ECC) functions, data retention (JESD47 compliant), Dynamic and Static Wear-Levelling & Bad Block Management.
- 5-year limited warranty or TBW whichever is earlier applies

SKU		INSSD256GM2230G3					
EAN	5055288449985						
	Width (mm)	Depth (mm)	Height	t (mm)	Weight (g)		
Product	22	0.8	3	30 2			
Packaging	55	12	ç	90 8			
Capacity			256GB				
Component For			Steam Deck, PCs, NUCs, ROG Ally, Microsoft Surface Pro Series, Dell, HP, Lenovo Ultrabooks & Tablets				
Form Factor				PCIe Gen3 x 4			
Mean time between failures (MTBF) (hour)				1000000			
TBW Rating				185			
Flash Type				TLC			
NVMe (Y/N)				Y			
S.M.A.R.T support (Y/N)				Y			
TRIM support (Y/N)				Y			
Read speed (MB per second)				3000			
Write speed (MB per second)				1800			
Operating Voltage (Volt)				3.3			
Power Consumption (Read) (Watt)				2.56			
Power Consumption (Write) (Watt)				2.29			
Hardware Encryption (Y/N)				N			

Interface	PCIe Gen3 x 4
Operating temperature (T-T) (Degrees Celcius)	070
Storage temperature (T-T) (Degrees Celcius)	-45 - 85
Sustainability Certificates	RoHS
Certification	UKCA, CE, FCC, RoHS