

Product Specification

64 GB Industrial SATA III 2.5" SSD



Integral 2.5 INCH SATA III SSD built with long-lasting Pseudo SLC (pSLC) flash memory and an extended temperature range for use in industrial applications.

- For use in 2.5 INCH SATA III SSD compatible industrial devices
- Extended temperature range for use in industrial applications
- Long-lasting Pseudo SLC (pSLC) flash memory

SKU	INIS2564GPSLC
EAN	5055288442283

	Width (mm)	Depth (mm)	Height (mm)	Weight (g)
Product	69.8	100.1	7	50
Packaging				

Capacity (GB)	64
Form factor	2.5"
ECC (Y/N)	Y
Mean time between failures (MTBF) (hour)	2000000
TBW rating	1058
Flash type	pSLC
NVMe (Y/N)	N
S.M.A.R.T. support (Y/N)	Y
TRIM support (Y/N)	Y
Read speed (MB per second)	519
Write speed (MB per second)	190
Operating voltage (Volt)	5
Hardware encryption (Y/N)	N

Interface	Serial ATA III
Operating temperature (T-T) (degrees Celcius)	-40 - 85
Storage temperature (T-T) (degrees Celcius)	-40 - 85
Sustainability certificates	RoHS
Certification	CE, FCC, UKCA