CAMERA 121W

The First *WIRELESS* Document Camera!

Teachers can now present lessons from anywhere in the room using a high resolution camera that does not have a single wire connected to it, completely wireless. The camera's images are transmitted to the classroom computer and can be displayed on a monitor, screen or Interactive Whiteboard.

Key Features:

- No Wires! (40 ft range) Self contained power
- Hi-Definition
 Document Camera
- Excellent Image Clarity and Color
- Camera has a Built-in LED Light
- Flexible Gooseneck Camera Design
- Simple Camera and Base Configuration
- 5 Year Unlimited Warranty
- Reliable Wireless using 802.11n Link
- Battery in base powers the camera
- Wired operation with a 25 ft. USB cable is also possible



Touchboards

205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

DUKANE Wireless Camera 121W



SPECIFICATIONS

 Product:
 No. 121W

 Description:
 Camera , Wireless, USB, High Resolution

 Components:
 Camera with flex neck, camera base unit with battery and wireless transmitter, dongle receiver for the PC , battery recharger power supply for the base unit

150Mbps

Wireless operation;

Type of link: Speed of link: Nominal operating time: Operating computer system

Wireless Dongle:

Camera signal input:

Camera Operation

Sensor Technology: Field of View: Output Resolution:

Zoom Capacity: Lamp: USB Output: Auto Exposure: Auto White Balance: Auto Focus: Auto Tune: Photo/Text Mode: Windows XP SP2, Vista, Window (not Mac) for wireless operation Thumb sized, USB port device, AW-NU120 Into the USB port on the computer via the dongle

IEEE 802.11n (2.4 GHz)

3 hours of wireless

CMOS 65 degrees XGA (1024 x 768), SXGA (1280x960),UXGA (1600x1200) using the USB port Frame Rate: 30 fps (Maximum), USB at 20fps 6x mechanical and 4x digital LED on camera head USB 2.0 High Speed Yes Yes Yes Yes

Select photo/text mode



Audio Visual Products

SPECIFICATIONS continued	
Image Capture:	Capture images to the computer via the USB port
Built-in Microphone:	Built into camera head for USB wired use only
Image Rotation:	Image rotation from 0 to 180 degrees
Annotation:	Yes, by using the included software
SOFTWARE Software Included:	Supports: Windows 7, XP, Vista , and Mac OSX.
Video Recording:	Record video with various compression codecs. Audio available only with wired USB cable link operation.
Image Capture:	Single or continuous capture of JPEG images, time lapse capture using settings
Annotation:	Add annotations directly to live or frozen image
Driver:	USB Driver Supports; TWAIN, UAC/ UVC for integration with interactive whiteboards including Promethean, SMART, Hitachi Starboard, Mimio, and others.
Mac operation:	With camera unit only using the USB cable. Mac OS 10.4 or better.
Camera and	
Base Anti-Theft:	Kensington lock port
Bolt Holes:	On Ccamera bottom for mounting: VESA standard 75 x 75 mm
Regulatory:	FCC-EMI, cUL, CE-EMC, CE-LVD, RoHS,
Camera unit	
Power:	From the base or the USB port
Size: Weight:	on computer 4.5" x 17" x 6" 2.2lbs
Base Unit	
Battery, Transmitter and Dongle:	Internal battery sealed and not user serviceable, antenna, dongle storage compartment
Pilot Indicator LEDs: Recharger Power:	LEDs for power on, charging, linked DC 12V , 3A max. From AC power unit for the Base supply
Size:	6″ x 2.5″ (3.8″ at antenna) x 8″
Weight:	1.0lbs.

Shipment Carton (W x H x D): Shipping weight Accessories included:

13.5" x 8" x 13.5" 6.5lbs. Quick start guides, CDs, USB cable assembly for 25ft. run, base recharger power supply, base to camera USB connector

Five (5) year limited warranty on parts and labor in North America. Provided by manufouter.

