



- Retail
- Restaurants
- Hospitality
- Healthcare
- Transportation
- Customer Experience
- Shopping
- Personal Kiosks
- Patient Entertainment
- Auto Dealers & Service
- Museums
- Libraries
- Hospitals
- Clinics
- Education
- Government Agencies
- DMV
- Labs
- Field & Tech Service Offices

Ergotron manages iPad devices for any facility or workflow



- Charge, sync and secure up to 48 iPad devices at once from one location
- Multiple cabinetry options:
Mobile cart for up to 32 or 48 iPad devices
Stationary desktop unit for up to 16 iPad devices
Wall mount station for up to 10 iPad devices
- Charge all devices simultaneously with one power cord to the wall socket
- Switch from charge to sync mode by connecting a Macintosh™ computer or PC
- Optional individual charge status indicators
- Designed for use with Apple® Configurator and iTunes®
- Small footprint keeps valuable space available
- Ventilated, enclosed storage keeps tablets safe and secure
- Durable, easy-to-clean exterior composed of high-grade fire-retardant ABS Secure Storage
- Steel tube and aluminum extrusion framework with durable locking steel doors



Certified for Safety

Ergotron not only uses UL-certified components, but goes a step further to have UL certify the entire system to guarantee safe use within the classroom, healthcare or enterprise setting. Tested and certified to UL standards, FCC requirements and all applicable country-specific regulations.

Carts are up to
**40%
smaller
and
lighter**
than competitive
offerings



Tablet Management
Cart 48



Tablet Management
Cart 32



Tablet Management
Desktop 16



Tablet Management
Wall Mount 10

For iPad		Tablet Management Cart 48		Tablet Management Cart 32		Tablet Management Desktop 16		Tablet Management Wall Mount 10	
Part # (color)	with ISI (black) US/CA/MX 24-329-085 UK/SING/HK 24-335-085 EU 24-341-085 AU 24-347-085 CN 24-353-085 JP 24-359-085 TH 24-411-085 KO 24-402-08	without ISI (black) UK/IE 24-377-085 EU 24-380-085	with ISI (black) US/CA/MX 24-328-085 UK/SING/HK 24-334-085 EU 24-340-085 AU 24-346-085 CN 24-352-085 JP 24-358-085 TH 24-410-085 KO 24-401-085	without ISI (black) US/CA/MX 24-373-085 UK/IE 24-376-085 EU 24-379-085	with ISI (black) US/CA/MX 24-327-085 UK/SING/HK 24-333-085 EU 24-339-085 AU 24-345-085 CH 24-351-085 JP 24-357-085 TH 24-409-085 KO 24-400-085	without ISI (black) US/CA/MX 24-372-085 UK/IE 24-375-085 EU 24-378-085	(silver/black) For 30-Pin iPad: US/CA/MX DM10-1001-1 EU DM10-1001-2 UK/SING/HK DM10-1001-3 AU/NZ DM10-1001-4 CN DM10-1001-5 JP DM10-1001-6	(silver/black) For Lightning iPad: US/CA/MX DM10-1002-1 EU DM10-1002-2 UK/SING/HK DM10-1002-3 AU/NZ DM10-1002-4 CN DM10-1002-5 JP DM10-1002-6	
30-pin Cable Options	Use 3 certified USB Cable Kits (97-766) or cables that come with device		Use 2 certified USB Cable Kits (97-766) or cables that come with device		Use 1 certified USB Cable Kit (97-766) or cables that come with device		Cables included		
Lightning Cable Options	Use cables that come with device Lightning Cable Kit (coming soon)		Use cables that come with device Lightning Cable Kit (coming soon)		Use cables that come with device Lightning Cable Kit (coming soon)		Cables included		
Onsite Professional Cable Integration	Product Integration Tier 2 (10+ units) US/CA/APAC w/o CN SRVCC-PI-02 CN SRVCC-PI-02 EMEA SRVCE-PI-02 Single Product Integration US only SRVC-SPI-01		Product Integration Tier 2 (10+ units) US/CA/APAC w/o CN SRVCC-PI-02 CN SRVCC-PI-02 EMEA SRVCE-PI-02 Single Product Integration US only SRVC-SPI-01		Product Integration Tier 1 (15+ units) US/CA/APAC w/o CN SRVCC-PI-01 CN SRVCC-PI-01 EMEA SRVCE-PI-01 Single Product Integration US only SRVC-SPI-01		Product Integration Tier 1 (15+ units) US/CA/APAC w/o CN SRVCC-PI-01 CN SRVCC-PI-01 EMEA SRVCE-PI-01 Single Product Integration US only SRVC-SPI-01		
ISI (Individual Status Indicators)	Yes	No	Yes	No	Yes	No	Yes		
Sync	Yes, USB or wireless		Yes, USB or wireless		Yes, USB or wireless		Yes, USB or wireless		
Charge	Yes, 2.1A via USB		Yes, 2.1A via USB		Yes, 2.1A via USB		Yes, 2.1A via USB		
# of Devices	48		32		16		10		
Security	Durable steel doors with three-point lock and assembly provide strong theft deterrence, steel tube and aluminum extrusion framework, optional Security Bracket accessory kit (97-735) provides ability to lock cart to floor or wall bracket for extra security when needed						Six-point lock assembly provides strong theft deterrence, includes security screws to attach unit to the wall		
Certification	Tested and certified to UL 60950-1 and UL 1667 standards, FCC requirements and all applicable country-specific regulations						Entire system certified to UL 60950-1 and UL 2442. Complies with FCC Part 15 Class A requirements		
Slot Size	7.9"H x 11.3"W x 0.85"D (20 x 28,8 x 2,2 cm)						≤ 10.2"H x 7.9"W x 0.9"D (25,9 x 20,1 x 2,3 cm)		
Product Dimensions	23"W x 18.4"D x 39.3"H (58,4 x 46,7 x 100 cm)		23"W x 18.4"D x 39.3"H (58,4 x 46,7 x 100 cm)		18.3"W x 16.2"D x 10.4"H (46,5 x 41,1 x 26,4 cm)		23.2"W x 31.8"H x 4.0"D (59 x 80,9 x 10,2 cm)		
Shipping Weight	152.5 lbs (69,2 kg)		126.5 lbs (57,4 kg)		35 lbs (15,8 kg)		39.5 lb (17,9 kg)		
Warranty	5 year warranty; 1 year warranty on all non-power supply electronic systems; 2 year warranty on all power units								