

# **Material Safety Data Sheet**

Trade Name as Used on Labeling	Product Code (First two digits of UPC No.)
Steel Shim	16
Arbor Spacers	24 & 38
Arbor Shims	25 & 39
Laminated Steel Shim	73
Date Prepared: 03/21/2011	Date reviewed: 08/03/2012

# **SECTION 1 – Chemical Product and Company Identification**

GHS Product Identification: Hot or Cold Rolled Steel Sheet/Strip and Hot Rolled Skelp Other means of identification: Carbon Steel Sheet/Strip and Skelp, Carbon Steel, HSLA Steel, Alloy Steel

CAS Number: Mixture

Supplier's Details: Precision Brand Products, Inc., 2250 Curtiss Street, Downers Grove IL 60515 USA

Phone Number (s): (630) 969-7200 (8:00 am - 4:00 pm CT) Fax: 630-969-0310

Emergency Phone Number: 1-800-424-9300 USA & Canada (202-483-7616 International) CHEMTREC

## SECTION 2 – Hazards Identification

As sold, this product, Hot or Cold Rolled Steel Sheet/Strip and Hot Rolled Skelp (semi-finished steel products) is not hazardous according to the criteria specified in European Directives 67/548/EEC and 1999/45/EC. Under 29 CFR 1910.1200 Hazard Communication Standard, steel products are considered mixtures due to further processing which may produce dusts and or fumes. Refer to Sections 3 and 8 for additional information. Refer to Section 11 for Toxicological Information.

Precautionary Statement/Emergency Overview: This formed solid metal product poses little or no immediate health or fire hazard. When product is subjected to welding, burning, melting, sawing, brazing, grinding, or other similar processes, potentially hazardous airborne particulate and fumes may be generated. In Dust state: Contact with water liberates extremely flammable gases. Irritating to skin, spontaneously flammable in air. These operations should be performed in well-ventilated areas. Avoid inhalation of metal dusts and fumes. Iron or steel foreign bodies imbedded in the cornea of the eye will produce rust stains unless removed fairly promptly. If appropriate, respiratory protection and other personal protective equipment should be used.

SECTION 3 – Composition / Information on Ingredients Chemical identity of the substance:						
Iron	231-096-4	7439-89-6	>86			
Aluminum	231-072-3	7429-90-5	2.0 max			
Copper	231-159-6	7440-50-8	2.5 max			
Chromium	231-157-5	7440-47-3	5.0 max			
Manganese	231-105-1	7439-96-5	3.0 max			
Molybdenum	231-107-2	7439-98-7	2.5 max			
Nickel	231-111-4	7440-02-0	5.0 max			
Silicon	231-130-8	7440-21-3	2.0 max			

EC – European Community

CAS – Chemical Abstract Service

All commercial steel products contain small amounts of various elements in addition to those listed. These small quantities are frequently referred to as "trace" or "residual" elements that generally originate in the raw materials used. Steel products may contain the following trace or residual elements including: boron, carbon, phosphorous, and sulfur.

# SECTION 4 – FIRST AID MEASURES

### Description of necessary first aid measures:

- Inhalation: If large amounts of dusts, fumes, or particulate are generated, move person to fresh air. If symptoms develop, seek medical attention.
- Eye Contact: For contact with dusts or particulate, flush eyes with water for 15 minutes. Eye injuries from solid particles should be treated by a physician immediately.
- Skin Contact: For skin contact with dusts or powders, wash immediately with soap and water. Cuts or abrasions should be treated promptly with thorough cleansing of the affected area.
- Ingestion: No need for first aid is anticipated if material is swallowed, however if symptoms develop, seek medical attention. For Ingestion of Dusts: IF SWALLOWED: Call a poison center or Doctor/physician if you feel unwell. Rinse mouth.

## Most important acute and chronic symptoms/effects:

**Primary Entry Routes**: Carbon steel products in their usual physical form do not present an inhalation, ingestion or contact hazard. However, operations such as burning, welding, sawing, brazing, machining and grinding may result in the following effects if exposures exceed recommended limits as listed in Section 8.

# SECTION 4 – FIRST AID MEASURES (continued)

#### Target Organs: Respiratory system. Acute Effects:

- Inhalation: Excessive exposure to high concentrations of dust may cause irritation to the eyes, skin and mucous membranes of the upper respiratory tract. Excessive inhalation of fumes of freshly formed metal oxide particles sized below 1.5 microns and usually between 0.02-0.05 microns from many metals can produce an acute reaction known as "metal fume fever". Symptoms consist of chills and fever (very similar to and easily confused with flu symptoms), metallic taste in the mouth, dryness and irritation of the throat followed by weakness and muscle pain. The symptoms come on in a few hours after excessive exposures and usually last from 12 to 48 hours. Long-term effects from metal fume fever.
- **Eye**: Excessive exposure to high concentrations of dust may cause irritation to the eyes. Particles of iron or iron compounds, which become imbedded in the eye, may cause rust stains unless removed fairly promptly.
- Skin: Skin contact with dusts may cause irritation or sensitization, possibly leading to dermatitis. Repeated or prolonged contact with oil residue may cause skin irritation, dermatitis or allergic reactions in sensitized individuals. Skin contact with metallic fumes and dusts may cause physical abrasion.

**Ingestion:** Ingestion of harmful amounts of this product as distributed is unlikely due to its solid insoluble form. Ingestion of dust may cause nausea or vomiting.

#### Acute Effects by component:

- Iron (and Iron Oxide): Iron is harmful if swallowed, causes skin irritation, and causes eye irritation. Contact with iron oxide has been reported to cause skin irritation and serious eye damage.
- Aluminum: Not Reported/Not classified
- Copper (and Copper Oxide): Copper may cause allergic skin reaction. Copper oxide is harmful if swallowed, causes skin and eye irritation, and my cause an allergic skin reaction.
- Chromium (as Hexavalent Chrome): Hexavalent chrome causes damage to gastrointestinal tract, lung, severe skin burns and eye damage, serious eye damage, skin contact may cause an allergic reaction, inhalation may cause allergic or asthmatic symptoms or breathing difficulties.
- Manganese (and Manganese Oxide): Manganese and Manganese oxide are harmful if swallowed.
- Molybdenum (and Molybdenum Oxide): Molybdenum causes skin and eye irritation. Molybdenum oxide is toxic if swallowed, and causes eye irritation.
- Nickel (and Nickel Oxide): Nickel may cause allergic skin sensitization. Nickel oxide may cause an allergic skin.
- Silicon: May be harmful if swallowed.

### Chronic Effects by component:

- IRON (as Iron Oxide): Chronic inhalation of excessive concentrations of iron oxide fumes or dusts may result in the development of a benign pneumoconiosis, called siderosis, which is observable as an X-ray change. No physical impairment of lung function has been associated with siderosis. Inhalation of excessive concentrations of ferric oxide may enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens. Iron oxide is listed as a Group 3 (not classifiable) carcinogen by IARC.
- ALUMINUM: Chronic inhalation of finely divided powder has been reported to cause pulmonary fibrosis and emphysema. Repeated skin contact has been associated with bleeding in the tissue, delayed hypersensitivity and granulomas. Chronic exposure to aluminum flake has been reported to cause pneumoconiosis in workers. Repeat oral exposure to aluminum results in decrements in neurobehavioral function and development.
- MANGANESE: Chronic exposure to high concentrations of manganese fumes and dusts may adversely affect the central nervous system
  with symptoms including languor, sleepiness, weakness, emotional disturbances, spastic gait, mask-like facial expression and paralysis.
  Animal studies indicate that manganese exposure may increase susceptibility to bacterial and viral infections. Occupational overexposure
  (Manganese) is a progressive, disabling neurological syndrome that typically begins with relatively mild symptoms and evolves to include
  altered gait, fine tremor, and sometimes psychiatric disturbances. May cause damage to lungs with repeated or prolonged exposure.
  Neurobehavioral alterations in worker populations exposed to MnO including: speed and coordination of motor function are especially
  impaired.
- **SILICON**: Silicon dusts are a low health risk by inhalation and should be treated as a nuisance dust. Eye contact with pure material can cause particulate irritation. Skin contact with silicon dusts may cause physical abrasion.
- CHROMIUM: The health hazards associated with exposure to chromium are dependent upon its oxidation state. The metal form (chromium as it exists in the product) is of very low toxicity. The hexavalent form is very toxic. Repeated or prolonged exposure to hexavalent chromium compounds may cause respiratory irritation, nosebleed, ulceration and perforation of the nasal septum. Industrial exposure to certain forms of hexavalent chromium has been related to an increased incidence of cancer. NTP (The National Toxicology Program) Fourth Annual report on Carcinogens cites "certain Chromium compounds" as human carcinogens. ACGIH has reviewed the toxicity data and concluded that chromium metal is not classifiable as a human carcinogen. Hexavalent chromium may cause genetic defects and is suspected of damaging the unborn child.
- COPPER: Inhalation of high concentrations of freshly formed oxide fumes of copper can cause metal fume fever. Chronic inhalation of copper dust has caused, in animals, hemolysis of the red blood cells, deposition of hemofuscin in the liver and pancreas, injury to lung cells and gastrointestinal symptoms.
- MOLYBDENUM: Certain handling operations, such as burning and welding, may generate both insoluble molybdenum compounds (metal
  and molybdenum dioxide) and soluble molybdenum compounds (molybdenum trioxide). Molybdenum compounds generally exhibit a low
  order of toxicity with the trioxide, the more toxic. However, some reports indicate that the dust of the molybdenum metal, molybdenum dioxide
  and molybdenum trioxide may cause eye, skin, nose and throat irritation in animals. Also has been reported to cause induction of tumors in
  experimental animals, suspected of causing cancer. Molybdenum oxide is suspected of causing cancer in humans.

# SECTION 4 – FIRST AID MEASURES (continued)

NICKEL: Exposure to nickel dusts and fumes can cause sensitization dermatitis, respiratory irritation, asthma, pulmonary fibrosis, edema and
may cause nasal or lung cancer in humans. Causes damage to lungs through prolonged or repeated inhalation exposure. IARC lists nickel
and certain nickel compounds as Group 2B carcinogens (sufficient animal data). <u>ACGIH 2009 TLVs<sup>®</sup> and BEIs<sup>®</sup></u> list insoluble nickel
compounds as confirmed human carcinogens. Suspected of damaging the unborn child.

Long-term inhalation exposure to high concentrations (over-exposure) to pneumoconiotic agents may act synergistically with inhalation of oxides, fumes or dusts of this product to cause toxic effects.

**Carcinogenicity:** IARC, NTP, and OSHA do not list steel products as carcinogens. IARC identifies welding fumes as a Group 2B carcinogen, a mixture that is possibly carcinogenic to humans. IARC identifies nickel and certain nickel compounds and welding fumes as Group 2B carcinogens that are possibly carcinogenic to humans. ACGIH lists insoluble nickel compounds as confirmed human carcinogens. IARC lists chromium metal and trivalent chromium compounds as Group 3 carcinogens, not classifiable as to their human carcinogenicity. Hexavalent chromium compounds are listed by IARC as Group 1 carcinogens that are carcinogenic to humans. NTP Fourth Annual report on Carcinogens cites "certain Chromium compounds" as human carcinogens. ACGIH has reviewed the toxicity data and concluded that chromium metal is not classifiable as a human carcinogen.

Medical Conditions Aggravated by Long-Term Exposure: Individuals with chronic respiratory disorders (i.e., asthma, chronic bronchitis, emphysema, etc.) may be adversely affected by any fume or airborne particulate matter exposure.

SARA Potential Hazard Categories: Immediate Acute Health Hazard; Delayed Chronic Health Hazard.

## Section 5 – Fire and Explosion Hazard Information

Suitable Extinguishing Media: Not applicable for solid product. Use extinguishers appropriate for surrounding materials. Specific Hazards arising from the chemical: Not applicable for solid product. Do not use water on molten metal. Explosion hazard: Accumulated metal dust can be combustible. Avoid creating dust. Do not use water on molten metal. Special protective equipment and precautions for fire fighters: Self-contained MSHA-NIOSH approved respiratory protection and full protective clothing should be worn when fumes and/or smoke from fire are present. Heat and flames cause emittance of acrid smoke and fumes. Do not release runoff from fire control methods to sewers or waterways. Firefighters should wear full face-piece self-contained breathing apparatus and chemical protective clothing with thermal protection. Direct water stream will scatter and spread flames and, therefore, should not be used.

## Section 6 – Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Not applicable to steel in solid state. For spills involving finely divided particles, clean-up personnel should be protected against contact with eyes and skin. If material is in a dry state, avoid inhalation of dust. Fine, dry material should be removed by vacuuming or wet sweeping methods to prevent spreading of dust. Avoid using compressed air. Do not release into sewers or waterways. Collect material in appropriate, labeled containers for recovery or disposal in accordance with federal, state, and local regulations.

Environmental precautions: Not applicable to steel in solid state. Follow applicable Federal, state, and local regulations. Methods and materials for containment and clean up: Collect material in appropriate, labeled containers for recovery or disposal in accordance with federal, state, and local regulations. Follow applicable OSHA regulations (29 CFR 1910.120) and all other pertinent state and federal requirements.

## Section 7 – Handling and Storage

**Precautions for safe handling:** Operations with the potential for generating high concentrations of airborne particulate should be evaluated and controlled as necessary. Practice good housekeeping. Avoid breathing metal fumes and/or dust. **Conditions for safe storage, including any incompatibilities**: Store away from acids and incompatible materials.

Section 8 – Exposure Controls/Personal Protection					
Ingredients	OSHA Pel <sup>1</sup>	ACGIH TLV <sup>2</sup>	NIOSH REL <sup>3</sup>	IDLH⁴	
Iron	10 mg/m <sup>3</sup> (as iron oxide fume)	5.0 mg/m <sup>3</sup> (as iron oxide dust and fume)	5.0 mg/m <sup>3</sup> (as iron oxide dust and fume)	2,500 mg Fe/m <sup>3</sup>	
Aluminum	15 mg/m <sup>3</sup> (as total dust, PNOR <sup>5</sup> ) 5.0 mg/m <sup>3</sup> (as respirable fraction*, PNOR)	10 mg/m <sup>3</sup> (as metal dust) 5.0 mg/m <sup>3</sup> (as welding fume)	10 mg/m <sup>3</sup> (as total dust) 5.0 mg/m <sup>3</sup> (as respirable dust)	NE	
Copper	0.1 mg/m <sup>3</sup> (as fume, Cu) 1.0 mg/m <sup>3</sup> (as dusts & mists, Cu)	0.1 mg/m³ (as fume) 1.0 mg/m³ (as dusts & mists, Cu)	1.0 mg/m³ (as dusts & mists)	100 mg Cu/m³	
Chromium	0.5 mg/m <sup>3</sup> (as Cr II & III, inorganic compounds) 1.0 mg/m <sup>3</sup> (as Cr, metal) 0.005 mg/m <sup>3</sup> (as Cr VI, inorganic compounds & certain water insoluble) "AL" 0.0025 mg/m <sup>3</sup> (as Cr VI, inorganic compounds & certain water insoluble)	0.5 mg/m³ (as Cr III, inorganic compounds) 0.5 mg/m³ (as Cr, metal) 0.05 mg/m³ (as Cr VI, inorganic compounds) 0.01 mg/m³ (as Cr VI, inorganic compounds & certain water insoluble)	0.5 mg/m <sup>3</sup> (as Cr II & III, inorganic compounds) 0.5 mg/m <sup>3</sup> (as Cr, metal) 0.001 mg/m <sup>3</sup> (as Cr VI, inorganic compounds & certain water insoluble)	2,500 mg/m³ (as Cr II & metal) 25 mg/m³ (as Cr III) 15 mg/m³ (as Cr Vi)	
Manganese	"C" 5.0 mg/m³ (as Fume & Mn Compounds)	0.2 mg/m³	"C" 5.0 mg/m³ 1.0 (as fume) "STEL" 3.0 mg/m³	500 mg Mn/m³	

	Section 8 – Exposure Controls / Personal Protection (Continued)						
Nickel	1.0 mg/m <sup>3</sup> (as Ni metal & insoluble compounds)	<ul> <li>1.5 mg/m³ (as inhalable fraction Ni metal)</li> <li>0.2 mg/m³ (as inhalable fraction Ni inorganic only insoluble and soluble compounds)</li> </ul>	0.015 mg/m <sup>3</sup> (as Ni metal & insoluble and soluble compounds)	10 mg/m³ (as Ni)			
Molybdenum	15 mg/m³ (as total dust, PNOR) <sup>5</sup> 5.0 mg/m³ (as respirable fraction, PNOR)	<ul> <li>10 mg/m<sup>3</sup> (as Mo insoluble compounds, inhalable fraction<sup>6</sup>)</li> <li>3.0 mg/m<sup>3</sup> (as Mo insoluble compounds, respirable fraction<sup>7</sup>)</li> <li>0.5 mg/m<sup>3</sup> (as Mo soluble compounds, respirable fraction)</li> </ul>	NE	NE			
Silicon	15 mg/m³ ( total dust, PNOR) <sup>3</sup> 5.0 mg/m³ (as respirable fraction, PNOR)	10 mg/m³	10 mg/m³ (as total dust) 5.0 mg/m³ (as respirable dust )	NE			

## NE – None established

Notes:

All commercial steel products contain small amounts of various elements in addition to those specified. These small quantities are frequently referred to as "trace" or "residual" elements that generally originate in the raw materials used. Steel products may contain the following trace or residual elements: antimony, arsenic, cadmium, cobalt, lead, tin and zirconium.

- OSHA PEL's (Permissible Exposure Limits) are 8-hour TWA (time-weighted average) concentrations unless otherwise noted. A ("C") designation denotes a ceiling limit, which should not be exceeded during any part of the working exposure unless otherwise noted. A Short Term Exposure Limit (STEL) is defined as a 15-minute exposure, which should not be exceeded at any time during a workday.
- 2.) Threshold Limit Values (TLV) established by the American Conference of Governmental Industrial Hygienists (ACGIH) are 8-hour TWA concentrations unless otherwise noted. ACGIH TLVs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes.
- 3.) The National Institute for Occupational Safety and Health Recommended Exposure Limits (NIOSH-REL) Compendium of Policy and Statements. NIOSH, Cincinnati, OH (1992). NIOSH is the federal agency designated to conduct research relative to occupational safety and health. As is the case with ACGIH TLVs, NIOSH REL's are for guideline purposes only and as such as no legal, regulatory limits for compliance purposes.
- 4.) The "immediately dangerous to life or health air concentrations value (IDLH's)" are used by NIOSH as part of the respirator selection criteria and were first developed in the mid-1970's by NIOSH. The Documentation for Immediately Dangerous to Life or Health Concentrations (IDLHs) is a compilation of the rationale and sources of information used by NIOSH during the original determination of 387 IDLHs and their subsequent review and revision in 1994.
- 5.) PNOR (Particulate Not Otherwise Regulated). All inert or nuisance dusts, whether mineral, inorganic, or organic, not listed specifically by substance name are covered by a limit which is the same as the inert or nuisance dust limit of 15 mg/m<sup>3</sup> for total dust and 5 mg/m<sup>3</sup> for respirable fraction.
- 6.) Inhalable fraction. The concentration of inhalable particulate for the application of this TLV is to be determined from the fraction passing a size-selector with the characteristics defined in the <u>ACGIH 2009 TLVs<sup>®</sup> and BEIs<sup>®</sup></u> (Biological Exposure Indices) Appendix D, paragraph A.
- 7.) Respirable fraction. The concentration of respirable dust for the application of this limit is to be determined from the fraction passing a size-selector with the characteristics defined in the <u>ACGIH 2009 TLVs<sup>®</sup> and BEIs<sup>®</sup></u> (Biological Exposure Indices) Appendix D, paragraph C.

**Appropriate Engineering Controls**: Use controls as appropriate to minimize exposure to metal fumes and dusts during handling operations. Provide general or local exhaust ventilation systems to minimize airborne concentrations. Local exhaust is necessary for use in enclosed or confined spaces. Provide sufficient general/local exhaust ventilation in pattern/volume to control inhalation exposures below current exposure limits.

#### Personal Protective Equipment (PPE):

**Respiratory Protection:** Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, use only a NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. Concentration in air of the various contaminants determines the extent of respiratory protection needed. Half-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 10 times the exposure limit. Full-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 50 times the exposure limit. Frotection by air-purifying negative-pressure and powered air respirators is limited. Use a positive-pressure-demand, full-face, supplied air respirator or self contained breathing apparatus (SCBA) for concentrations above 50 times the exposure is above the IDLH (Immediately dangerous to life or health) for any of the constituents, or there is a possibility of an uncontrolled release or exposure levels are unknown, then use a positive-demand, full-face, supplied air respirator with escape bottle or SCBA.

Warning! Air-purifying respirators both negative-pressure, and powered-air do not protect workers in oxygen-deficient atmospheres.

## Section 8 – Exposure Controls / Personal Protection (Continued)

## Protective Clothing/Equipment:

- Eyes: Wear appropriate eye protection to prevent eye contact. For operations, which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulate, use safety glasses to prevent eye contact. Contact lenses should not be worn where industrial exposures to this material is likely. Use safety glasses or goggles as required for welding, burning, sawing, brazing, grinding, or machining operations.
- Skin: Wear appropriate personal protective clothing to prevent skin contact. Cut resistant gloves and sleeves should be worn when working with steel products. For operations, which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulate, use protective clothing, and gloves to prevent skin contact. Protective gloves should be worn as required for welding, burning or handling operations.
- Other protective equipment: An eyewash fountain and deluge shower should be readily available in the work area.

Section 9 – Physical and Chemical Properties				
Appearance and Odor: Metallic Gray, Odorless	Water Solubility: Insoluble			
Odor Threshold: NA	Fat Solubility: NA			
Vapor Pressure: NA	Other Solubilities: NA			
Vapor Density (Air=1): NA	Boiling Point: ND			
Formula Weight: ND	Viscosity: NA			
Density: 7.85 g/cc	Refractive Index: NA			
Specific Gravity (H2O=1,60°F): NA	Surface Tension: NA			
pH: NA	% Volatile by volume: NA			
Flash Point (closed cup): NA	Evaporation Rate: NA			
Auto-Ignition Temperature: NA	Freezing Point: NA			
Decomposition Temperature: ND	Melting Point: ~2750 °F (~1510°C)			
Partition Coefficient n-octanol/water: ND	UEL: NA			
Flammability (solid, gas): Non-flammable, non-combustible	LEL: NA			
Explosive Properties: ND	Oxidizing Properties: ND			
NA- Not applicable				
ND- Not determined for product as a whole				

## Section 10 – Stability and Reactivity

Reactivity: Not determined (ND) for product as a whole.

Stability: Steel products are stable under normal storage and handling conditions.

Polymerization: Hazard polymerization cannot occur.

**Chemical Incompatibilities:** Will react with strong acids to form hydrogen. Iron oxide dusts in contact with calcium hypochlorite evolve oxygen and may cause an explosion.

**Conditions to Avoid:** Storage with strong acids or calcium hypochlorite.

Hazardous Decomposition/Combustion Products: Thermal oxidative decomposition of steel products can product fumes containing oxides of iron and manganese as well as other alloying elements.

Sensitivity to Mechanical Impact: ND

Sensitivity to Static Discharge: ND

#### Section 11 – Toxicological Information

Toxicological information has not been established for this product as sold. However, processing of this product in operations such as hightemperature (burning, welding), sawing, brazing, machining and grinding may produce fumes and/or particulate, which would result in the material being classified as hazardous under OSHA 29 CFR 1910.1200. The categories of Health Hazards as defined in "<u>Globally Harmonized System of</u> <u>Classification and Labeling of Chemicals (GHS), Third revised edition ST/SG/AC.10/30/Rev. 3</u>" United Nations, New York and Geneva, 2009 have been evaluated and are listed below:

POTENTIAL HAZARD	HAZARD CATEGORY	HAZARD SYMBOL	SIGNAL WORD	HAZARD STATEMENT
Acute Toxicity Hazard	4 <sup>a</sup>	!	Warning	Harmful if swallowed
Skin Irritation	1 <sup>b</sup>	I E	Danger	Causes severe skin burns
Eye Damage/Irritation	1 <sup>c</sup>	I PE	Danger	Causes severe eye damage
Skin Sensitization	1 <sup>d</sup>	!	Warning	May cause an allergic skin reaction
Respiratory Sensitization	1 <sup>e</sup>		Warning	May cause allergy or asthma symptoms or breathing difficulties if inhaled
Germ Cell Mutagenicity	1B <sup>f</sup>		Danger	May cause cancer
Carcinogenicity	1A <sup>g</sup>	*	Danger	May damage fertility or the unborn child
Toxic Reproduction	2 <sup>h</sup>	-	Warning	Causes damage to lungs Causes damage to respiratory and gastrointestinal tracts

	Section 11 – T	oxicologica	I Information	(Continued)
pecific Target Organ Systemic Toxicity STOST) following Single Exposure	3 <sup>i</sup>		Warning	May cause respiratory irritation
pecific Target Organ Systemic Toxicity STOST) following Repeated Exposure	1 <sup>j</sup>	*	Danger	Causes damage to lungs and central nervous system throu prolonged or repeated inhalation exposure. Causes dama to skin, mucosal membranes and lungs through all
·		v		exposures.
otes:	for Hot or Cold Pollo	d Stool Shoot/Str	in and Hat Pallad	Skalp (comi finished steel producte) The following date has
<ul> <li>No LC<sub>50</sub> or LD<sub>50</sub> has been established been determined for the components</li> </ul>		a steel sneet/str	ip and not Kolled	Skelp (semi-finished steel products). The following data has
Aluminum Oxide: LD <sub>50</sub> =>50			• Iron:   Dro =	1060 mg/kg (Oral/Rat)
<ul> <li>Copper Oxide: LD<sub>50</sub> = 470 m</li> </ul>				<b>m Oxide:</b> $LD_{50} = 83 \text{ kg/mg}$ (Oral/Rat)
<ul> <li>Chromium (as Cr<sup>+VI</sup>): LD<sub>50</sub> =</li> </ul>	80 mg/kg (Oral/Rat)			$_0 > 9000 \text{ mg/kg}$ (Oral Rat): LC <sub>50</sub> > 10.2 mg/l (Inhalation/Rat)
<ul> <li>Iron Oxide: LD<sub>50</sub> = 10,000 mg</li> </ul>	g/kg (Oral/Rat)			le: LD <sub>50</sub> > 5000 mg/kg (Oral/Rat)
Manganese: Mn single oral e		from 275 to		$_{50} = 3160 \text{ mg/kg}$ (Oral/Rat); and as <b>Silicon Dioxide</b> : LD <sub>50</sub> >
804 mg/kg body weight per da	ay for manganese chlo	ride in different	15,000 mg/k	kg (Oral/Rat); LD <sub>50</sub> > 5000 mg/kg (Dermal/Rat); LC <sub>50</sub> > 0.69
rat strains.				halation/Rat)
			Strip and Hot Roll	led Skelp (semi-finished steel products) as a mixture. The
following Skin (Dermal) Irritation infor			0	
<ul> <li>Iron, Copper Oxide, Molybd</li> <li>Iron oxide: Moderately initiation</li> </ul>		itation		ay cause allergic skin reaction. It is reported that copper may
<ul> <li>Iron oxide: Moderately irritati</li> <li>Chromium (as Cr<sup>+VI</sup>): Corros</li> </ul>		tizor Cousos	Molybdenu	gic contact dermatitis in susceptible individuals.
<ul> <li>Chroman (as cr. ). Conos severe skin burns.</li> </ul>		lizer. Gauses	•	ht irritation only in rabbits.
Copper, Molybdenum: Irritat	ina.		•	le: Human skin sensitizer
		I Sheet/Strip and		(semi-finished steel products) as a mixture. The following Ey
Irritation information was found for the		•	-	
<ul> <li>Iron, Copper Oxide, Molybd</li> </ul>	enum: Irritating		Chromium	(as Cr <sup>+VI</sup> ): Corrosive
<ul> <li>Iron oxide: Severely irritating</li> </ul>			<ul> <li>Nickel: Slig</li> </ul>	ht eye irritation from particulate abrasion only.
Molybdenum Oxide: Causes				ght eye irritation in rabbit protocol
				t Rolled Skelp (semi-finished steel products) as a mixture. T
following Skin (Dermal) Sensitization			ts:	
<ul> <li>Nickel, Nickel Oxide: May ca</li> <li>Copper, Chromium (as Cr<sup>+V</sup></li> </ul>	Ause allergic skin serisi	lization.		
e. No Respiratory Sensitization data ava	ailable for Hot or Cold	Rolled Steel She	et/Strin and Hot R	colled Skelp (semi-finished steel products) as a mixture. The
following Respiratory Sensitization data ave				
<ul> <li>Chromium (as Cr<sup>+VI</sup>): Occup</li> </ul>				
			/Strip and Hot Ro	Iled Skelp (semi-finished steel products) as a mixture. The
following Mutagenicity and Genotoxic	ity information was fou	nd for the compon	ents:	• • • • •
Aluminum and Aluminum O	xide: IUCLID; ATSDR	have found this in	gredient is not mut	agenic in vitro; but has marginal effects in vivo.
<ul> <li>Nickel: EU RAR has found per</li> </ul>				ssification.
Nickel Oxide: ATSDR has for	ound positive and nega	tive results in vitro	and <i>in vivo</i> .	
Chromium (as Cr <sup>**</sup> ): SCOE	L has found positive in	in vitro and in vivo	assays including	cell transformation in vitro and dominant lethal in vivo.
Iron and Iron Oxide: IUCLIE				et Delle d'Oleche (e en i finish e d'ete al mer durte) de service e en
g. Carcinogenicity: IARC, NTP and OS The following Carcinogenicity information			Sheet/Strip and Ho	ot Rolled Skelp (semi-finished steel products) as carcinogen
Welding fumes: IARC Group			carcinogenic to h	umans
				arcinogenic to humans. Insoluble nickel compounds – ACGI
				genic potential in animals or humans; suspect carcinogen
				ategory 1a, may cause cancer. Human data in which exposu
to nickel refinery dust caused	•			· · · · ·
				ot classifiable as to their human carcinogenicity. Hexavalent
				ium metal – ACGIH not classifiable as a human carcinogen.
NTP Fourth Annual report on				
				ted to cause induction of tumors in experimental animals. Skelp (semi-finished steel products) as a mixture. The
following Toxic Reproduction data available			-P and not Koneu	
			ts may cause delav	in development of neurobehavioral indices.
<ul> <li>Hexavalent Chromium: EUI</li> </ul>		•		•
				experimental animals caused fetotoxicity.
1 0 0 ,		0 0 1		for Hot or Cold Rolled Steel Sheet/Strip and Hot Rolled
				ure data was found for the components:
Iron, Copper Oxide, Molybd	· ·		0,	0 1 2
0		ation following sin	gie innalation expo	sures to a 2.8-43 mg/m³ for manganese dioxide or manganes
tetroxide particulate in rodent		ing Repeated Eva	osure data was ave	ailable for Hot or Cold Rolled Steel Sheet/Strip and Hot
				ed Exposure data was found for the components:
• •	,	•	•	chronic exposure to aluminum flake has been reported to cau
				e to aluminum results in decrements in neurobehavioral funct
and development.		-	•	
Hexavalent Chromium: EU-	SCOEL listed as Categ	ory 1, has found ir	nflammation of lung	g, skin irritation and ulceration with repeat exposures in worke
				havioral alterations in worker populations with Mn and MnO
including: speed and coordina				
<ul> <li>Manganese Oxide: CICADS</li> </ul>	i listed as Category 2, I	has tound signs of	lung inflammation	in rhesus monkeys exposed via inhalation to 0.7 mg/m <sup>3</sup>
	liouido for 00 hours	day avar 10 '	ha	
manganese, as manganese o				al by inhalation at 1 mg/m <sup>3</sup> for 00 days daysland lime
<b>u</b>	U-RAR listed as Catego			el by inhalation at 1 mg/m³ for 90 days developed lung

-	· · · - ·				
Sec	ction 11 – Toxico	ological Informa	ation (Continued)		
Section 11 – Toxicological Information (Continued) The above toxicity information was determined from available scientific sources to illustrate the prevailing posture of the scientific community. The scientific resources include: The American Conference of Governmental Industrial Hygienists (ACGIH) Documentation of the Threshold Limit Values (TLVs) and Biological Exposure indices (BEIs) with Other Worldwide Occupational Exposure Values 2009, The International Agency for Research on Cancer (IARC), The National Toxicology Program (NTP) updated documentation, the World Health Organization (WHO) and other available resources, the International Uniform Chemical Information Database (IUCLID), European Union Risk Assessment Report (EU-RAR), Concise International Chemical Assessment Documents (CICAD), European Union Scientific Committee for Occupational Exposure Limits (EU-SCOEL), Agency for Toxic Substances and Disease Registry (ATSDA), Hazardous Substance Data Bank (HSDB), and International Programme on Chemical Safety (IPCS).					
	Section 12 -	- Ecological Inf	ormation		
Hazard Category : 3 Hazard Symbol: No symbol Signal Word: No signal word Hazard Statement: Harmful to aquatic life Ecotoxicity: No data available for the product, Ho individual components of the product have been for follows:					
<ul> <li>Iron Oxide: LC<sub>50</sub> &gt; 1000 mg/L; Fis</li> </ul>	h				
<ul> <li>Nickel Oxide: LC<sub>50</sub> &gt; 100 mg/l; in fi</li> </ul>		ae			
<ul> <li>Aluminum Oxide: LC<sub>50</sub> &gt; 100 mg/l</li> </ul>					
Hexavalent Chrome: EU RAR liste		cute EC <sub>50</sub> and LD <sub>50</sub> to a	algae and invertebrates < 1	mg.	
<ul> <li>Nickel Oxide: IUCLID found LC<sub>50</sub> i</li> </ul>	n fish, invertebrates and	algae > 100 mg/l.	5	0	
Mobility: No data available for the product, Hot o			d Skelp (semi-finished stee	el products) as a whole. However.	
individual components of the product have been for					
Persistence & Degradability: No Data Available					
Bioaccumulative Potential: No Data Available					
Note: The listing of regulations relating to a Precis	sion Brand Products, Inc.	steel product may not	be complete and should no	t be solely relied upon for all regulatory	
compliance responsibilities.		, ,	·	, , , , ,	
	Section 13 -	<b>Disposal Cons</b>	iderations		
Dispersely. Other Learning should be assurable double and				also he assured as also find has a	
Disposal: Steel scrap should be recycled wheney				also be recycled, or classified by a	
competent environmental professional and dispos					
Container Cleaning and Disposal: Follow applic					
16-01-17 (ferrous metals), 12-01-99 (wastes not o					
Please note this information if for Hot or Cold Rolled S information.	teel Sheet/Strip and Hot Ko	blied Skeip (semi-finished	steel products) in its origina	form. Any alterations can void this	
	Section 14	- Transport Inf	ormation		
		ortation Data (49 CFR			
US Department of Transportation (DOT) under 49					
products) as a hazardous material. All federal, sta				material must be adhered to.	
Shipping Name: Not applicable (NA)	Packaging Authoriza		Quantity Limitations	- ( - D - 11	
Shipping Symbols: NA	a.) Exceptions: N/	4		raft or Railcar: NA	
Hazard Class: NA	b.) Group: NA		b.) Cargo Aircraft O		
UN No.: Not applicable	c.) Authorization:	NA	Vessel Storage Require		
Packing Group: NA			a.) Vessel Storage:	NA	
DOT/IMO Label: NA Special Provisions (172.102): NA			b.) Other: NA		
The International Maritime Dangerous Goods (IMI	C) and the Regulations	Concorning the Interne	DOT Reportable Quant		
packaging and shipping requirements follow the U			alonal Carriage of Dangeron	us Goods by Rail (RID) classification,	
ADR – Regulations Concerning the International C			t regulate Het or Cold Bol	ad Stool Shoot/Strip and Hot Pollod	
Skelp (semi-finished steel products) as a hazardo	0 0		regulate not of Cold Rol	led Steel Sheet/Strip and Hot Kolled	
Shipping Name: Not applicable (NA)	Packaging		Portable Tanks & Bulk	Containers	
Classification Code: NA	a.) Packaging Inst	tructions: NA	a.) Instructions: NA		
UN No.: Not applicable		g Provisions: NA	b.) Special Provisions: NA		
Packing Group: NA	· ·	Provisions: NA	.,		
ADR Label: NA	,				
Special Provisions: NA					
Limited Quantities: NA					
IATA – International Air Transport Association (IA	TA) does not regulate He	ot or Cold Rolled Stee	el Sheet/Strip and Hot Rol	led Skelp (semi-finished steel products) as	
a hazardous material.			-		
Shipping Name: Not Applicable (NA)	Passenger & Cargo A	Aircraft Limited	Cargo Aircraft Only	Special Provisions:	
Class/Division: NA	Quantity (EQ)		Pkg Inst: NA	NA	
Hazard Label: NA	Disc in etc. N/A	Pkg Inst: NA	Max Net Qty/Pkg: NA	ERG Code: NA	
UN No.: NA					
	Pkg Inst: NA Max Net Oty/Pkg:				
Packing Group: NA	Max Net Qty/Pkg:	Max Net Qty/Pkg:			
Excepted Quantities (EQ): NA	Max Net Qty/Pkg: NA	Max Net Qty/Pkg: NA			
Excepted Quantities (EQ): NA Pkg Inst – Packing Instructions Max Net C	Max Net Qty/Pkg: NA tty/Pkg – Maximum Net O	Max Net Qty/Pkg: NA Quantity per Package	ERG – Emergency Resp		
Excepted Quantities (EQ): NA           Pkg Inst – Packing Instructions         Max Net C           Transport Dangerous Goods (TDG) classification:	Max Net Qty/Pkg: NA tty/Pkg – Maximum Net O	Max Net Qty/Pkg: NA Quantity per Package			
Excepted Quantities (EQ): NA Pkg Inst – Packing Instructions Max Net C	Max Net Qty/Pkg: NA Ity/Pkg – Maximum Net ( Hot or Cold Rolled Stee	Max Net Qty/Pkg: NA Quantity per Package el Sheet/Strip and Hot	t Rolled Skelp (semi-finishe		
Excepted Quantities (EQ): NA           Pkg Inst – Packing Instructions         Max Net C           Transport Dangerous Goods (TDG) classification:	Max Net Qty/Pkg: NA Ity/Pkg – Maximum Net ( Hot or Cold Rolled Stee	Max Net Qty/Pkg: NA Quantity per Package	t Rolled Skelp (semi-finishe		

upon for all regulatory compliance responsibilities. This product and/or its constituents are subject to the following regulations: OSHA Regulations: Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-2, Z-3): The product, Hot or Cold Rolled Steel Sheet/Strip and Hot Rolled Skelp (semi-finished steel products) as a whole is not listed. However, individual components of the product are listed: Refer to Section 8, Exposure Controls and Personal Protoction Protection.

				ory Information (Continued)
		Id Rolled Steel S	heet/Strip and Hot Rolled Skelp	o (semi-finished steel products) is not listed as a whole. However, individual componen
of the product are	listed:			
Components Copper		Regulations CWA, SARA		
Manganese		SARA 313, C		
Chromium			SARA 313, SDWA	
Nickel		CAA, CWA, S		
SARA Potential H	lazard Cate	gories: Immediate	e Acute Health Hazard; Delayed	Chronic Health Hazard
Regulations Key				
			412; 40 CFR Part 61 [As of: 8/18	
	302.4 and A		a Response, Compensation and	Liability Act (42 USC secs. 9601(14), 9603(a); 40 CFR Sec 302.4, Table 302.4, Table
			cs. 1311: 1314(b).(c).(e). (a): 136	6(b), (c); 137(b),(c) [as of 8/2/06])
			very Act (42 USC Sec. 6921;I 40	
				302 Extremely Hazardous Substances (42 USC secs. 11023, 13106; 40 CFR Sec.
				23, 13160; 40 CFR 372.65 [as of 6/30/05])
			(15 U.S.C. s/s 2601 et seq. [1976 J.S.C.s/s 300f et seq. [1974])	D])
				hemicals subject to the reporting requirements of section 313 of Title III of the Superful
			and 40 CFR part 372:	
	AS #	Chemical Name		nht
	440-50-8	Copper	2.5 max	<u></u>
	440-47-3	Chromium	5.0 max	
	439-96-5	Manganese	3.0 max	
	440-02-0	Nickel	5.0 max	
			hat are copied and distributed for th	nis material. Iot Rolled Skelp (semi-finished carbon steel) as a whole is not listed in any state
Minnesota: Copp Massachusetts: M Dther regulation	er, Chromio Vanganese s: ation (Can	um, Nickel, Manga , Copper, Chromit adian): Hot or Co	Im, Molybdenum, Sulfur, and Nic nese, Silicon, Molybdenum, and Im, Nickel, and Molybdenum Id Rolled Steel Sheet/Strip and	
Ingredi			lassification	
Iron			, D2B	
			,	
Copper		Dž	B, B4	
Manganese		B4	, D2A	
Molybdenum		B4	, D2B	
Nickel		1	D2B	
Silicon		+	B4	
		final in an and the		extended Developer Development and the MODO
his product has			with the hazard criteria of the Co	ontrolled Products Regulations and the MSDS contains all the information required by
	Judoto ricgi		Section 16 -	Other Information
azardous Material	Identificatio	on System (HMIS) C		National Fire Protection Association (NFPA)
lealth Hazard		1		
	_			•
Fire Hazard		0		
Physical Haza	rd	0		$\checkmark$
rritation or minor rev FIRE = 0, Materials t PHYSICAL HAZARE	versible injury that will not b 0 = 0, Materia	<sup>,</sup> possible. urn ils that are normally s	arne dusts or fumes are generated. table, even under fire conditions, and If-react. Non-explosives.	HEALTH = 1, Exposure could cause irritation but only minor residual injury even if no treatment given. FIRE = 0, Materials that will not burn INSTABILITY = 0, Normally stable, even under fire exposure conditions, and are not reactive wi water.
the date h that individ	ereof. How duals recei	vever, Precision B ving the informati	and Products, Inc. makes no repon will exercise their independe	data believed to be reliable. It is provided in good faith and is believed to be correct as presentation as to the comprehensiveness or accuracy of the information. It is expect ant judgment in determining its appropriateness for a particular purpose. According s of any kind resulting from the use of or reliance upon such information.

that individuals receiving the information will exercise their independent judgment in determining its appropriateness for a particular purpose. Accordingly, Precision Brand Products, Inc. will not be responsible for damages of any kind resulting from the use of or reliance upon such information. NO REPRESENTATIONS, OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER TO WHICH THE INFORMATION REFERS. The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment.