

ENO® PROJECTOR KIT SPECIFICATIONS

Projector and mount solution for the eno interactive whiteboard.



STEELCASE PJ930 PROJECTOR

Panel Size / resolution	0.65" WXGA, S450, DDP4421
Technology	DLP
Throw ratio	Ultra short throw 0.35
Lumens	3000 (standard) 2450 (eco)
Contrast ratio	2300:1
Resolution	WXGA, XGA
Aspect ratios	16:10 (Native) 4:3 16:9
Lamp life	5,000 hours (standard) 8,000 hours (eco)
Power button	Yes
3D Ready	Yes
Speaker(s)	10W (two speakers)
Color wheel	6 segment (RGBCYW)
Noise level	33dB (standard) 29dB (eco)
Power supply	AC input 100~240 +/- 10% voltage
Power consumption	290W (standard) 260W (eco) <0.5W (standby)

LED Indicator	Power LED: Green Temp LED: Red Lamp LED: Amber
Input signal	Data: VESA Standard HDTV: 1080i / 720p / 1080p DTV: 480i / 480p Video: NTSC/NTSC 4.43 PAL B/G/H/I, SECAM
Terminal I/O	Computer in: VGA (2), Display Port Computer out: VGA Video in: Video, S-Video, HDMI (1.4) Audio in: Mini jack, RCA R/L Audio out: Mini jack Microphone: Phone jack
Control I/O	Network management: RJ45 USB (upgrades) Room control: RS232
Temperature	Non-operating: -10 ~ 60 degree C Operating: 5 ~ 40 degree C
Altitude	Non-operating: Sea level ~ 30,000 FT Operating: Sea level ~ 10,000 FT @23 degree C
Humidity	Non-operating: 5% ~ 95% (no condensation) Operating: 10% ~ 85% (no condensation)
Accessories	Power cord: 4.5m VGA cable: 4.5m Remote control User Manual (CD)
Lamp replacement	While mounted Part No. 23354001SR
Remote control replacement	Part No. 23354101SR
Kensington Lock Slot	Yes
Warranty	3 year - Warranty excludes products considered by Steelcase to be consumables (e.g., batteries, lamps, except projector lamps offer 6 months coverage)
Dimensions	Device: 11.3" x 14.7" x 4.9" (288 x 375 x 126 mm) 11 lb (5 kg) Shipping: 11" x 20" x 17" (279 x 508 x 432 mm) 17.6 lb (8 kg)

PEERLESS PSTA600 MOUNT

Fully integrated cable management systems conceals and protects cables for a clean finish

Model number	Peerless PSTA-600
Finish	Aluminum alloy, powder coat
Weight	8.5 lbs (3.8kg)
Max load	25 lbs (11.3 kg)
Certifications	UL listed (US and Canada) for masonry and wood-studded walls
Warranty	Limited 5 year warranty
Dimensions	Mount: 25.0" x 9.6" x 10.6" (635 x 244 x 271mm) Shipping: 21.0" x 12.0" x 11.0" (533 x 305 x 279 mm) 10.5 lb (4.7 kg)
Package Contents	Ultra short throw arm, end cap, PSRGS-UNV, installation hardware, assembly instructions



205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Steelcase®

Call 800.333.9939 or visit steelcase.com

Item #13-0000581 8/13 ©2013 Steelcase Inc. All rights reserved. All specifications subject to change without notice. Trademarks used herein are the property of Steelcase Inc. or of their respective owners. Printed in U.S.A. FSC certified.