





Rev 05/02/14 RMC





## 🎡 🚿 🍙 🔂 🕅 TAA

## A-B. iTeach<sup>®</sup> Tablet Charging/Syncing Carts

- Easily charge and transport up to 32 tablet devices with this modern and attractive cart. Combining modern aesthetics with tried and true functionality, this versatile design holds 32 iPads or other mobile computing devices in one secure and portable unit.
- Controlled power management knows which tablets need more power, providing a safe and secure way to keep your tablets up to speed, extending battery life and saving energy.
- Designed for easy accessibility, the ergonomic placement of the charging slots means no getting on your hands and knees to load and unload. Plug works with many popular tablets equipped with a USB charging cable.
- Sliding top shelf locks to protect your tablets. Top also serves as a standing height work surface, remaining stable even when open.
- Upgrade to the new charge and sync cart and keep your tablets synced to a host computer. Sync via iTunes or a Windows host computer using the sync USB cable provided.
- Apple devices can be configured using the Apple Configurator app available directly from Apple, and synced using iTunes. Non-Apple devices will appear as USB drives and can sync via dragging and dropping. Contact your tablet manufacturer for the best method of transferring files on your specific device.
- Powder-coated steel body with coordinating HPL/edge banding. Durable 5" swivel casters (two locking). Slots hold tablets up to .96" thick, accommodating most tablets even with a case.
- Tested and approved for Electromagnetic Compatibility to FCC 47 CFR Part 15; ICES-003, Issue 4 (2004) -FCC 47 CFR Part 15.107 Conducted Emissions and FCC 47 CFR Part 15.109 Radiated Emissions.
- Ten year warranty on cart. Two year warranty on electrical. TAA compliant. Ships fully assembled.

| Key                                  | Part No. | Item                                  | Dimensions           | Ship Wt. |  |
|--------------------------------------|----------|---------------------------------------|----------------------|----------|--|
| iTeach Tablet Charging/Syncing Carts |          |                                       |                      |          |  |
| Α                                    | 27670    | iTeach Tablet Charging Cart           | 36"H x 26"W x 34.5"D | 245 lbs  |  |
| в                                    | 27679    | iTeach Tablet Charging + Syncing Cart | 36"H x 26"W x 34.5"D | 245 lbs  |  |

All trademarks and registered trademarks are the property of their respective owners.

| Item                                 | Specification   |  |
|--------------------------------------|---|--|
| Body Material                        | Powder-coated steel   |  |
| Tablet Compartments                  | LED light indicators for charge time and/or sync status at each slot. Slots measure 12.26"H x 8.2"W x .96"D.  |  |
| Handles                              | Full width angular handle for maneuvering, fits through all standard doorways   |  |
| Capacity                             | 32 tablets or other mobile computing devices  |  |
| Recommended Devices                  | Versions of the Apple iPad, Apple iPad Mini, Kindle Fire, Barnes & Noble Nook,<br>HP TouchPad, Dell Streak, Samsung Galaxy. Call for assistance with specific<br>device compatibility.  |  |
| Input                                | 100-120 VAC at 12.5 Amps, 60 Hz   |  |
| Output                               | 32 x 5 VDC at 2.1A  |  |
| Profile                              | Automatic charger emulation profile cycling for USB-IF BC1.2DCP (Android),<br>YD/T-1591 (Apple iPad and iPhone), and RIM (Blackberry) devices. Firmware is<br>upgradable for future devices. Contact MooreCo for firmware update options. |  |
| Certification                        | EC 60950-1  |  |
| Ambient Operating Temperature        | 32° to 95° F (0° to 35° C)  |  |
| Ambient Non-operating<br>Temperature | -4° to 113° F (-20° to 45° C)   |  |
| Relative Humidity                    | 5% to 95% non-condensing  |  |
| Dimensions                           | 36"H x 26"W x 34.5"D  |  |
| Exterior                             | Auxiliary four-outlet power strip with on/off switch  |  |
| Weight                               | 245 lbs   |  |
| Cord                                 | 6 ft power cord   |  |
| Warranty                             | 10 year cart / 2 year electrical  |  |
| Shipping                             | Ships fully assembled   |  |
| LED Indicator Details                | 1 red LED: No device charging   |  |
|                                      | 1 blue LED: Device charging for less than 1.5 hours   |  |
|                                      | 2 blue LEDs: Device charging between 1.5 and 3 hours  |  |
|                                      | 3 blue LEDs: Device charging between 3 and 4.5 hours  |  |
|                                      | 4 blue LEDs: Device charging more than 4.5 hours  |  |
|                                      | Upper/Lower Blue: Syncing (syncing cart only)   |  |



Balt<sup>®</sup> & Best-Rite<sup>®</sup> are brand divisions of MooreCo, Inc.

2885 Lorraine Ave | Temple, TX 76501 p: 800.749.2258 | f: 800.697.6258

www.moorecoinc.com