

iTeach[®]
Desktop Sync/Charger

Touchboards
205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com


mooreco


balt
Best-Rite



 **iTeach**[®]
www.moorecoinc.com



Sync and charge up to eight tablet devices right on your desktop with this compact unit.


www.moorecoinc.com



A-B. iTeach® Desktop Sync/Charger

- Easily charge and/or sync up to eight USB tablet or phone devices right on your desktop with the compact and attractive iTeach® Desktop Sync/Charger.
- Controlled power management knows which devices need more power, helping to extend battery life and saving energy. Includes four charge indicators and on/off power switch.
- Charge or sync up to eight devices with one power cord to the wall. Unit works with most tablets and other devices that are charged via USB.
- USB port in the back of unit is used to sync to a master device, or daisy chain several together using a USB hub.
- Optional syncing mode can be accessed via an iTunes or Windows 7 host computer using the sync USB cable provided.
- Apple devices can be setup and configured using the Apple Configurator available directly from Apple and synced using iTunes. Non-Apple devices will appear as USB drives and can sync via dragging and dropping. Contact your tablet manufacturer to understand the best method of transferring files for your specific device.
- TAA compliant.

Key	Part No.	Description	Dimensions	Ship Wt.
iTeach Desktop Sync/Charger				
A	27690*	Charger	7"H x 16.5"W x 14"D	15 lbs
B	27704*	Sync & Charger	7"H x 16.5"W x 14"D	15 lbs

Made in Taiwan.

*Ships UPS

All trademarks and registered trademarks are the property of their respective owners.

Item	Specification
Body	Powder-coated steel
Tablet Compartments	Five or six stage LED light indicators. LED attached/detached indicator. Slots measure 12.26"H x 8.2"W x .96"D.
Capacity	8 tablets or other mobile computing devices
Recommended Devices	Versions of the Apple iPad, Apple iPad Mini, Kindle Fire, Barnes & Noble Nook, HP TouchPad, Dell Streak, Samsung Galaxy. Call for assistance with specific device compatibility.
Input	100-120 VAC at 12.5 Amps, 60 Hz
Output	8 x 5 VDC at 2.1A
Profile	Automatic charger emulation profile cycling for USB-IF BC1.2 DCP (Android), YD/T-1591 (Apple iPad and iPhone), and RIM (Blackberry) devices. Firmware is upgradable for future devices. Contact MooreCo for firmware update options.
Ambient Operating Temperature	32° to 95° F (0° to 35° C)
Ambient Non-operating Temperature	-4° to 113° F (-20° to 45° C)
Relative Humidity	5% to 95% non-condensing
Dimensions	7"H x 16.5"W x 14"D
Weight	15 lbs
Exterior	On/off switch
Cord	9 ft power cord
Warranty	2 year electrical
Shipping	Ships fully assembled
LED Indicator Details	1 red LED: No device charging
	1 blue LED: Device charging for less than 1.5 hours
	2 blue LEDs: Device charging between 1.5 and 3 hours
	3 blue LEDs: Device charging between 3 and 4.5 hours
	4 blue LEDs: Device charging more than 4.5 hours
	Upper/Lower Blue: Syncing (syncing model only)



Balt® & Best-Rite® are brand divisions of MooreCo, Inc.

2885 Lorraine Ave | Temple, TX 76501
p: 800.749.2258 | f: 800.697.6258

www.moorecoinc.com